imageCLASS X



1440i

Intuitively Efficient

DESIGNED FOR A PRODUCTIVE WORKFLOW

Experience quality printing with the new and compact **1440i**. Designed for intuitive operation and ease of use, this Multifunction Device (MFD) offers fast performance at up to 40 pages/min for A4 single-sided printing and high security, making it perfect for any office.

Canon

COMPACT SIZE

Designed with a small footprint to keep space efficient and streamline operations.

- 01 Lower Device Height with new Automatic Document Feeder design.
 - 2 Flushed UI Screen for a clean look.



EASY OPERABILITY

Use different tabs for prints and customise printing with an easy drag-and-drop feature.



Prin Stre

)))

Print File from Server Streamline routine operations through printing documents from shared folders at a tap.

Connectivity

Boost productivity with uniFLOW Online. Print connectivity through mobile is also possible with AirPrint and Mopria for greater convenience.

SECURE AND RELIABLE

The 1440i comes with the latest security features, so you can have a peace of mind.



Encrypted Secure Print Reduce the risk of information leakage by sending encrypted printing data to the device.



User Authentication Prevents data leaks by limiting access to only authorised personnel.



Verify System at Start Up Verifies the integrity of the firmware and applications when the device starts up.

Business Can Be Simple

imageCLASS X

Specifications

MAIN UNIT			PRINT SPECIFICATIONS			
Machine Type	Monochrome A4 Laser Multi-functional		Print Speed (BW)	1-sided: 40.0 pages/min (A4)	2-sided: 33.6 pages/min (A4)	
Core Functions	Print, Copy, Scan, Send		Print Resolution (dpi)	600 × 600		
Control Panel	127 mm (5 inch) TFT LCD WVGA Colour Touch panel		Page Description	Standard: UFR II, PCL6, PCL5, Adobe PostScript 3		
Memory	1.0GB RAM		Languages			
Storage	2GB		Direct Print	Direct printing available from USB memory Supported file types: TIFF, JPEG, PDF		
Interface Connection						
	1000Base-T/100Base- TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n), Wi-Fi Direct Connection	USB 2.0 (Host) x2, USB 2.0 (Device) x1	and Cloud Application (optional) OS Standard Printing	Universal Print Android / Windows® 10 / Windows® 11 / Chrome OS / macOS (11.2.2)		
Memory Media	USB Memory			/ iOS / iPadOS (As of March 2023)		
Network Security	TLS 1.3, IPSec, IEEE802.1X authentication, SNMPv3, Firewall Functionality (IP/MAC Address Filtering), Enabling/Disabling (Network Applications, Remote UI, USB Interface), USB Port separation from LAN		Operating System	UFRII: Windows® 10/11, Server 2012/Server 2012 R2/Server 2016/ Server 2019/Server 2022, MAC OS (10.13 or later) *Windows® (As of February 2023) / MAC OS (As of March 2023) PCL: Windows® 10/11, Server 2012/Server 2012 R2/Server 2016/Server 2019/Server 2022 *Windows® (As of February 2023) PS: Windows® 10/11, Windows®Server 2012/Server 2012 R2/Server 2016/Server 2019/Server 2022, MAC OS (10.13 or later) *Windows® (As of February 2023) / MAC OS (As of March 2023) PPD: Windows® 10/11, MAC OS (10.13 or later) *Windows® 10/11, MAC OS (10.13 or later)		
Document Security	Print Security (Secure Print, Encrypted Secure Print, uniFLOW Secure Print'), Scan Security' ² (Encrypted PDF, Device Signature PDF/XPS), Send Data Security (Restricted E-mail/File send functions, Allow/Restrict Sending from History) ¹ Requires optional uniFLOW Online ² Requires optional PDF SECURITY-E1					
Paper Supply Capacity	Standard Cassette: 250 sheets					
(A4, 80g/m ² gsm)	Multi-purpose tray: 100 sheets Maximum: 900 sheets (with Cassette Feeding Module-AH1x1)					
Paper Output Capacity	y 65 sheets		COPY SPECIFICATIONS			
(A4, 80g/m ² gsm)			Copy Speed	1-sided: up to 40.0 pages/min (A4) 2-sided: up to 33.6 pages/min (A4)	
Supported Media Sizes	Standard Cassette Standard size: A4, A5, A5R, A6, B5 Custom size: 105.0 x 148.0 mm up to 216.0 x 355.6 mm	Multi-purpose tray Standard size: A4, A5, A5R, A6, B5, Index Card, Envelope: [No. 10 (COM10), Monarch, ISO-C5, DL] Custom size: 76.2 x 127.0 mm up to 216.0 x	First-Copy-Out Time (BW)	Approx. 6.1 seconds or less (A4)	,	
			Copy Resolution (dpi)	300 x 600 (DEF) 600 x 600		
			Multiple Copies	Up to 999 copies		
		355.6 mm	Copy Density	Automatic or Manual (9 levels)		
Supported Media Weights	Standard Cassette: 60 to 120g/m² gsm Multi-purpose tray: 60 to 199g/m² gsm Duplex: 60 to 120g/m² gsm		Magnification	25% - 400% (1% increments) Preset reduction / enlargement: 25%, 50%, 70%, 100%, 141%, 200%, 400%		
Warm-up Time	From Power On: 14 seconds or less*		SCAN SPECIFICATIONS			
(Quick Start Mode: N/A)	*Time from device power-on, until copy ready (not print reservation)		Туре	1 PDS		
	From Sleep Mode: 4 seconds or less		Document Feeder Paper	Up to 50 sheets		
Dimensions (W x	420.0 x 460.0 x 375.0 mm		Capacity (A4, 80g/m ² gsm)			
D x H)			Supported Media Sizes	A4R, A5R, A6R, B5R Custom size: 48.0 × 85.0 mm to 216.0 x 355.6 mm		
Installation Space (W x D)	420.0 x 881.0 mm *Cassette and back door opened		Scan Speed	Copy (300 × 600 dpi) 1-sided scanning (BW): 40 / 20 2-sided scanning (BW): 80 / 40		
Weight *Without Toner	Standard: approx. 15.6 kg		(ipm: BW/CL; A4)			
PAPER SUPPLY OPTION	PAPER SUPPLY OPTIONS			Send (300 × 300 dpi)		
Cassette Feeding Module-AH1	Paper capacity: 550 sheets (80 gsm) Paper size: A4, A5, A5R, A6, B5 Custom size: 105.0 x 148.0 mm to 216.0 x 356.0 mm Dimensions (W x D x H): 399.0 x 356.0 x 131.0 mm Weight: approx. 3.8 kg			1-sided scanning (BW): 50 / 40 2-sided scanning (BW): 100 / 80		
			Scan Resolution (dpi)	Copy: up to 600 x 600 Send: (Push) up to 300 x 600, (Pr		
ENVIRONMENTAL SPECIFICATIONS		Pull Scan Specifications	ScanGear MF For both TWAIN and WIA			
Power Source	220-240V, 50/60Hz, 3.1A		SEND SPECIFICATIONS	E-mail/Internet FAX (SMTP), SME) ETD	
Power Consumption	Maximum: approx. 1280W or less		Destination Address Book /	LDAP (50) / Local (300) / Speed	•	
HARDWARE ACCESSORIES (OPTIONAL)			Speed Dials	20, (30) / 200al (300) / 3peed		
MiCARD Attachment Kit-B1 Copy Card Reader Attachment-J1			Send Resolution (dpi)	Push: 192 x 204 (I-FAX) 300 x 300 (email/SMB/FTP	Pull: Max. 9 600 x 9 600	
Send PDF Security Feature Set-E1 Barcode Printing Kit-E1 Copy Control Interface Kit-C1			Communication Protocol	File: FTP (TCP/IP), SMB3.0 (TCP/I Email/iFax: SMTP (Send), POP3 (F		
			File Format	Standard: TIFF, JPEG*, PDF (Compact, Searchable) Optional: PDF (Encrypted, Digital Signature) *Single page only		



CANON INDIA PVT. LTD.

Delighting You Always

7th Floor, Tower B, Building #5, DLF Epitome Building, DLF Phase III, Gurugram-122002 Ph.: 0124-4160000 | Fax: 0124-4160011 | Web: in.canon

DEALER'S STAMP

This document is for information purposes only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.