

Canon's PTZ remote camera CR-N700 is a high-end 4K PTZ remote camera which is capable of fulfilling advanced workflows in the production, sports broadcasting and AR/VR production through the new 12G-SDI terminal, night mode and Free-d protocol. And with add-on licenses, you can enjoy features like auto tracking and auto loop.

New DIGIC DV7 Processor

The new DIGIC DV7 image processor with Canon's 25.4mm (1.0 inch) CMOS sensor are optimised to deliver outstanding image quality with exceptional low light performance and



additional new features such as eye/head detection AF, HLG/PQ HDR, diffraction correction and much more.

4K 60P Image Quality

The CR-N700 is a versatile, high-end production camera that supports 4K 60P video output, while a new 12G-SDI terminal enables multi output of 4K 60P video for high-end production needs such as smoother playback and slow-motion effects.

Night Shooting Via IR

The CR-N700 helps you to capture natural scenes in the dark. Infrared mode makes it possible to film a variety of shows such as reality shows or animal observations in their natural habitats.





EOS's Intelligent Autofocus Tracking

EOS iTR AF X and Eye AF technologies, as well as Dual Pixel CMOS AF technology, enable the CR-N700 remote camera



to seamlessly track your talent, ensuring that even when they move and are obstructed by other people or objects, the camera will keep them in focus.

Eye Detection AF

Even when another subject appears in the foreground, the camera will remain focused on the targeted subject's eye and closely tracks it to continue shooting while maintaining accurate focus.



Face/Head Detection AF

The Canon EOS iTR AF X allows the camera to keep tracking the subject if they turn their face around from the camera. By using deep learning, this feature can help improve the quality of your images.





Crop Function

The crop feature streams a number of views from various angles, allowing viewers a more immersive experience.

With CR-N700's crop function, users can output entire video along with cropped portions simultaneously.



Cropping can be set for up to two locations, output in FHD or HD Crop resolution.

Zooming is also possible on cropped images.



Output terminal 1: Full-screen output



Output terminal 2: Crop 1

Multi Output

The CR-N700 features a 12G-SDI output terminal that can stream 4K 60P video with a single cable. When used together with the 3G-SDI terminal, users can now output two video channels simultaneously.

This means a single camera can output video for different purposes at the same time, answering video production needs by combining various assist functions.





Free-d and SRT Protocols

The CR-N700 supports Free-d and SRT protocols in addition to a number of other protocols such Canon XC Protocol, RTSP/RTP, NDI|HX, and RTMP/RTMPS.

The CR-N700 can be easily integrated in virtual production applications such as news, weather forecasts, sports and live events thanks to Free-d protocol, which enables them to directly feed in real time the Pan, Tilt, Zoom, Focus and Iris, as well as the position of the PTZ Camera into a virtual platform such as unreal engine.





The CR-N700 supports the SRT Protocol which enables high-quality, low-latency and secure video streaming even over unstable public networks.



SPECIFICATIONS		
Sensor/Lens		25.4mm (1in) 4K 15x Dual Pixel CMOS AF
Advanced Zoom		Yes
IR Mode		Yes (Monochrome)
Video Output I/F		12G-SDI, 3G-SDI, HDMI, IP
Video Output Format [Maximum]	SDI	12G-SDI: 4K 59.94p (4:2:2 10 bit) 3G-SDI: FHD 59.94p (4:2:2 10 bit)
	HDMI	4K 59.94p (4:2:2 10 bit)
	IP	4K 59.94p (4:2:0 8 bit)
HDR		Yes (HLG/PQ)
Log Shooting		Yes
Face Tracking AF		Yes (Face/Head/Eye)
Image Stabilisation		Yes (Optical)
Video Transfer Protocol (IP)		XC Protocol/RTP (RTSP)/RTMP (S)/NDI HX/SRT
Control Protocol (IP/Serial)		XC Protocol/Standard Communication (Serial/IP)/NDI HX/Free-d
Power Supply		POE++, DC12V (XLR connector)
Time Code Terminal		Yes
Pan Operation Range/Speed		±170°, 0.1°/s - 100°/s
Tilt Operation Range/Speed		-30° - 90°, 0.1°/s - 100°/s
Crop Function		Yes

30x Advanced Zoom

The CR-N700 is equipped with 15x optical zoom starting from 25.5mm. Using the 4K sensor during FHD, it can shoot at a maximum of approximately 30x advanced zoom while maintaining image quality.








Add-On Applications System

The CR-N700 supports Canon's Add-On Application Systems which allow Canon PTZ remote cameras to enhance video production by adding advanced features through the installation of paid applications. The system now incorporates Auto Tracking and Auto Loop Applications.

Auto Tracking



CR-N700 offers excellent hardware responsive for in-camera auto tracking of subject, with various levels of configuration such as tracking sensitivity, priority display area, or composition for tracking subject.



Supporting two repeated movements and fade mode, Auto Loop application automates a portion of visual creative work, allowing directors and operators to concentrate on switching and camera framing.

OR FULL SPECIFICATIONS, PLEASE REFER TO OUR WEBSITE

AUTHORIZED DEALER'S STAMP