

Powerful and Swift Printing

FOR GREATER RESULTS

Start every workday with confidence. The LBP325x monochrome laser printer makes high volume printing effortless. Small in footprint, easy to maintain and scalable for greater productivity, the LBP325x is ready whenever the business gears up for growth.







HIGH CAPACITY Add up to three 550-sheet cassettes for a huge paper input capacity of 2 300 sheets, reducing the frequency of paper reloads.



HIGH SPEED

Featuring speeds of 43pages/min and 36pages/min for single-sided and double-sided prints respectively, boost your print productivity rate with LBP325x.

Business Can Be Simple



MINIMAL MAINTENANCE

Experience effortless replacement with the All-in-One Cartridge and the Auto Toner Seal

uniFLOW COMPATIBLE

Track print usage with uniFLOW print



EASE OF USE

Experience friendly navigation of settings with the 5-line LCD with numeric keys. Print directly from your USB device.

SPECIFICATIONS

PRINT			
Printing Method		Monochrome Laser Beam Printing	
Printing Speed	A4	43 pages/min	
	Letter	45 pages/min	
	2-sided	36 pages/min (A4) / 37 pages/min (Letter)	
Print Resolution		600 x 600dpi	
Print Quality with Image Refinement Technology		1200 (eq.) x 1200dpi (eq.)	
Warm up Time (From Power On)		30 s or less	
First Printout Time (FPOT)	A4	Approx. 5.7 s	
	Letter	Approx. 5.7 s	
Recovery Time (From Sleep Mode)		3.0 s or less	
Print Language		UFR II, PCL 6, PostScript 3™	
Auto Duplex Print		Standard	
Available Paper Size for Auto Duplex Print		A4, Letter, Legal, Foolscap, Indian Legal	
Print Margins		5mm - top, bottom, left and right (Envelope: 10mm)	
Print Features		Poster, Booklet, Watermark, Page Composer,	
Print reatures		Toner Saver	
USB Direct Print		Supported	
Supported File Format for USB Direct Print		Supported File Format: JPEG, TIFF, PDF	
PAPER HANDLING			
	Standard Cassette	550 sheets	
Paper Input	Multi-Purpose Tray	100 sheets	
(Based on 80g/m ²)	Optional Paper Feeder	550 sheets (x3)	
Maximum Paper Input Capacity		2 300 sheets	
Paper Output		250 sheets	
	Cassette / Optional Paper Feeder	A4, B5, A5, A6, Letter, Legal, Statement, Executive,	
		Foolscap, Indian Legal, Custom	
		(Min. 105.0 x 148.0mm to Max. 216.0 x 355.6mm)	
Paper Sizes	Multi-Purpose Tray	A4, B5, A5, A6, Letter, Legal, Statement, Executive,	
		Foolscap, Indian Legal, Index Card	
		Envelope: COM10, Monarch, C5, DL, Custom	
		(Min. 76.2 x 127.0mm to Max. 216.0 x 355.6mm)	
Paper Types		Plain, Heavy, Recycled, Label, Index Card,	
Coursetter (Postcard, Envelope	
Paper Weight	Cassette / Optional Paper Feeder	60 to 120g/m ²	
	Multi-Purpose Tray	60 to 199g/m ²	
CONNECTIVITY & SOFTWA		00 t0 1999/11	
CONNECTIVITI & SOFTWA		USB 2.0 High Speed, 10Base-T/100Base-TX	
Standard Interfaces	Wired	/1000Base=T	
	Wireless		
Network Protocol	Print	LPD, RAW, WSD-Print (IPv4,IPv6)	
		Bonjour(mDNS), HTTP, HTTPS, POP before SMTP	
	TCP/IP Application Services	(IPv4,IPv6), DHCP, ARP+PING, Auto IP, WINS (IPv4),	
		DHCPv6 (IPv6)	
	Management	SNMPv1, SNMPv3 (IPv4, IPv6)	
		. ,	

Network Security	Wired	IP/Mac address filtering, HTTPS, SNMPv3, IEEE802.1x, IPSEC
	Wireless	-
Other Features		Department ID, Secure Print
		Canon PRINT Business, Canon Print Service, Google
Mobile Solution		Cloud Print [™] , Apple [®] AirPrint [®] , Mopria [®] Print Service
Compatible Operating Systems		Windows [®] 10, Windows [®] 8.1, Windows [®] 7,
		Windows Server® 2019, Windows Server® 2016,
		Windows Server® 2012 R2, Windows Server® 2012,
		Windows Server® 2008 R2, Windows Server® 2008,
		Mac [®] OS X 10.9.5 & up ^(*1) , Linux ^(*1)
Software Included		Printer driver, Toner Status
GENERAL		
Device Memory		1 GB
LCD Display		Vari-Angle 5-line LCD
Dimensions (W x D x H)		417 x 376 x 275 mm
Weight		Approx. 11.5 kg (without cartridge)
	Maximum	1 380 W or less
Power Consumption	Operation (average)	Approx. 600 W
	Standby (average)	Approx. 10.1 W
	Sleep (average)	Approx. 1.9W (USB)/ Approx. 1.2 (LAN)
Noise Levels (*2)	Operation	Sound Pressure Level: 54dB
		Sound Power Level: 6.9B
	Standby	Sound Pressure Level: 26dB
		Sound Power Level: 3.9B
	Temperature	10 - 30°C
Operating Environment	Humidity	20% - 80% RH (no condensation)
Power Requirements		AC 220 - 240V (+/-10%), 50/60 Hz (+/-2Hz)
Toner Cartridge (*3)	Standard	Cartridge 056: 10 000 pages (bundled: 5 100 pages)
	Low	Cartridge 056L: 5100 pages
	High	Cartridge 056H: 21 000 pages
Monthly Duty Cycle (*4)		150 000 pages
OPTIONAL ACCESSORIES		
Paper Feeder		Paper Feeder PF-C1 (550 sheets)
Barcode Printing		Barcode Printing Kit-F1
SD Card		SD Card - C1

Linux can be downloaded from and declared per ISO 9296. nce with ISO /IEC 19752. es a means of comparison for product robustness in relation to other Canon es a means of comparison for product robustness in relation to other Canon es a means of usal maximum image output per month.



CANON INDIA PVT. LTD.

7th Floor, Tower B, Building #5, DLF Epitome Building, DLF Phase III, Gurugram-122002 Ph.: 0124-4160000 | Fax: 0124-4160011 | Web: in.canon

Dealer's Stamp