



Drive Productivity with High Speed and Volume Printing

Experience formidable print productivity and performance with the new **imageCLASS LBP361dw**. Featuring a rapid print speed of up to 61 pages/min, robust print security, scalable paper input capacity and versatile connectivity features – ideal for business and enterprise environments.

UP TO
61 Pages/Min
(A4)
FAST PRINT
SPEED

QUICK
4.9 s
FIRST PRINT
OUT TIME


WIRELESS
CONNECTIVITY


+4
PAPER FEEDER
(OPTION)

MONO
UP TO **27 000**
PAGES
CARTRIDGE YIELD



EXPANDABLE PAPER CAPACITY

Meet growing business needs with an expandable paper capacity of up to 4 300 sheets and work efficiently with less printing downtime.



MULTIPLE PRINT ENVIRONMENT SUPPORT

In addition to Canon's proprietary UFR II print language, industry standard PCL6 and Adobe® PostScript® 3™ print languages are supported to ensure seamless integration with a wide range of business applications.



SECURE & SEAMLESS CONNECTIVITY

With Dual Network Support, you can now share the printer across two different networks simultaneously. This enables administrators to perform network segmentation without compromising on security.



ENHANCED DATA PROTECTION

TLS 1.3 encrypts and protects data from sniffing, spoofing and tampering, while the system's integrity can be monitored during startup.

SPECIFICATIONS / imageCLASS LBP361dw

PRINT	Printing Method		Monochrome Laser Beam Printing	
	Print Speed	A4	61 pages/min	
		Letter	65 pages/min	
		2-Sided	50 images/min (A4) / 53 images/min (Letter)	
	Print Resolution		600 x 600 dpi	
	Print Quality with Image Refinement Technology		1200 x 1200 dpi (Equivalent)	
	Warm-Up Time (From Power On)		22 s	
	First Print Out Time (FPOT) (Approx.)	A4	4.9 s	
		Letter	4.9 s	
	Recovery Time (From Sleep Mode)		2.0 s or less	
	Print Language		UFR II, PCL 6, Adobe® PostScript® 3™	
	Auto Duplex Print		Yes	
	Print Margins		Top/Bottom/Left/Right margin: 5 mm Top/Bottom/Left/Right margin: 10 mm (Envelope)	
	Supported File Format for USB Direct Print		JPEG, TIFF, PDF, XPS	
PAPER HANDLING	Input Tray Capacity (Plain paper, 80 g/m²)	Standard	Cassette	550 sheets
			Multi-Purpose Tray	100 sheets
		Optional	Paper Feeder	550 sheets (x3)
			Paper Deck	2 000 sheets (x1)
		Maximum		4 300 sheets (Standard + 3 Paper Feeders + 1 Paper Deck)
	Output Tray Capacity (Plain paper, 80 g/m²)		500 sheets	
	Media Size	Cassette / Paper Feeder		A4, A5, A6, B5, B6, Legal, Letter, Executive, Statement, Foolscap, Government Letter, Government Legal, Indian Legal, Custom (min. 99 x 148 mm to max. 216 x 355.6 mm)
		Multi-Purpose Tray		A4, A5, A6, B5, B6, Legal, Letter, Executive, Statement, Foolscap, Government Letter, Government Legal, Indian Legal, Index Card, Envelope (COM10, Monarch, DL, C5), Custom (min. 76.2 x 127 mm to max. 216 to 355.6 mm)
		Paper Deck		A4, Legal, Letter
		2-Sided Printing		A4, A5, B5, Legal, Letter, Executive, Foolscap, Government Letter, Government Legal, Indian Legal
	Media Type		Plain Paper, Recycled Paper, Colour Paper, Label, Postcard, Envelope	
	Media Weight	Cassette / Paper Feeder / Paper Deck		60 – 135 g/m ²
		Multi-Purpose Tray		60 – 199 g/m ²
		2-Sided Printing		60 – 120 g/m ²

CONNECTIVITY & SOFTWARE	Standard Interface	Wired	USB 2.0 High Speed, 10Base-T/100Base-TX/1000Base-T	
		Wireless	Wi-Fi 802.11b/g/n (Infrastructure Mode, WPS, Direct Connection)	
	Network Protocol	Print	TCP/IP (LPD/RAW/IPP/IPPS/FTP/WSD)	
		TCP/IP Application Services	Bonjour (mDNS), HTTP, HTTPS, POP before SMTP (IPv4, IPv6), DHCP, Auto IP, WINS (IPv4), DHCPv6 (IPv6)	
		Management	SNMPv1, SNMPv3 (IPv4, IPv6)	
	Network Security	Wired	IP/Mac address filtering, SSL (HTTPS, IPPS), SNMPv3, IEEE802.1X, IPsec, TLS 1.3, Dual Network Support	
		Wireless	Infrastructure Mode: WEP (64/128 bit), WPA-PSK (TKIP/AES), WPA2-PSK (TKIP/AES), WPA3-SAE (AES), WPA-EAP (AES), WPA2-EAP (AES), WPA3-EAP (AES), IEEE802.1X Access Point Mode: WPA2-PSK (AES)	
	Other Features		Department ID, Forced Hold Printing, Secure Print	
	Mobile Solution		Canon PRINT Business, Canon Print Service, Apple® AirPrint®, Mopria® Print Service, Microsoft Universal Print	
	Compatible Operating Systems¹		Windows®, Windows Server®, Mac® OS, Linux ¹	
	Software Included		Printer Driver, Toner Status	
	Device Memory		2 GB	
	Display		5-Line LCD with Vari-Angle	
	Power Requirements		AC 220 – 240 V, 50/60 Hz	
Power Consumption (Approx.)	Operation	772 W (max. 1500 W)		
	Standby	13.7 W		
	Sleep	1 W		
Operating Environment	Temperature	10 – 30°C		
	Humidity	20% – 80% RH (no condensation)		
Monthly Duty Cycle²		275 000 pages		
Dimensions (W x D x H) (Approx.)		430 x 465 x 370 mm		
Weight³ (Approx.)		20 kg		
TONER CARTRIDGE⁴	Toner Cartridge⁴	Standard	Cartridge 073: 27 000 pages (bundled: 11 500 pages)	
		Low	Cartridge 073L: 11 500 pages	
	Paper Feeder	Paper Feeder PF-J1		
Paper Deck	Paper Deck PD-H1			
Envelope Feeder	Envelope Feeder EF-B1			

¹ For version details of compatible operating systems and to download the latest available device drivers, please visit <https://asia.canon.com/support>

² Monthly Duty Cycle value provides a means of comparison for product robustness in relation to other Canon laser printer devices, and does not refer to actual maximum image output per month.

³ Excluding toner cartridge.

⁴ Toner cartridge yield is in accordance with ISO/IEC 19752.



CANON INDIA PVT. LTD.

7th Floor, Tower B, Building #5, DLF Epitome Building, DLF Phase III, Gurugram-122002
Ph.: 0124-4160000 | Fax: 0124-4160011 | Web: in.canon

DEALER'S STAMP	This document is for information purpose only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.
-----------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------