





# Built for **Business**

# Unleash Productivity with A3 Monochrome Laser Printer for the Modern Office

Streamline your workflow, reduce costs and elevate your office performance with the imageCLASS LBP468x. Designed for efficiency, the printer boasts robust paper handling capabilities that accomodate a wide range of media types and sizes, making it the ideal choice for all your printing needs.











## EXPANDABLE PAPER CAPACITY

Designed to meet your growing business demands, this printer features an expandable paper capacity up to 2,550 sheets. Perfect for managing high volume printing tasks while minimising the need for frequent paper replenishment.



#### MULTIPLE PRINT ENVIRONMENT SUPPORT

addition Canon's In to proprietary UFR ll, the printer also supports PCL 6 industry-standard PostScript® and Adobe® 3™ print languages. This robust compatibility ensures seamless integration with a wide range of business applications.



### SECURE & SEAMLESS CONNECTIVITY

With Dual Network, you can share the printer across two separate networks simultaneously. This enables administrators to perform network segmentation while maintaining robust security.



TLS 1.3 encrypts and protects data from sniffing, spoofing and tampering, as well as allowing the system's integrity to be monitored during startup.



#### SPECIFICATIONS/imageCLASS LBP468x

	CIFICATIONS/ima	geclass	LBP408X				1	
	Printing Method			Monochrome Laser Beam Printing		Standard	Wired	USB 2.0, 10Base-T/100BaseTX/ 1000Base-T
		A4*1		45 prints/min	Interfaces	Wireless	IEEE 802.11b/g/n (Infrastructure Mode, Access Point Mode)	
	Print Speed	Letter*1		44 prints/min	-	Network Protocol	Print	TCP/IP (LPD, RAW, IPP, IPPS, FTP, WSD)
		2-Sided A4		42.1 images/min	-			IP/Mac Address Filtering, HTTPS, SNMPv3,
	A3			22.5 prints/min			Wired	IEEE 802.1X, IPsec, TLS 1.3, Dual Network Support
	Print Resolution			600 x 600 dpi 1 200 x 1 200 dpi	LWA	Network Security	Wireless	Infrastructure Mode: WEP (64/128 bit), WPA-PSK (TKIP/AES), WPA2-PSK (TKIP/AES), WPA3-SAE (AES), WPA2-PSK (TKIP/AES), WPA3-SAE (AES), WPA3-EAP (AES), WPA3-EAP (AES), WPA3-EAP (AES), UEEE 802.1X, Access Point Mode: WPA2-PSK (AES)
Ĭ	Print Quality with Image Refinement Technology			1 200 x 1 200 dpi (equivalent)	& SOF			
PRINT	Warm-Up Time (From Power On)			22 s or less	Τ			
	First Print Out Time*2 (approx.)	A4		7 s	CONNECTIVITY & SOFTWARE	Mobile/Cloud Printin	ng Solutions	Canon PRINT, Canon Print Service (Android), AirPrint®, Mopria® Print Service
	Recovery Time (From Sleep Mode)			7 s or less	Ŭ			Microsoft Universal Print
	Print Language			UFR II, PCL 6, Adobe® PostScript® 3™		Operating System C	Compatibility*4	Windows 10/11, Windows Server 2016/2019/2022, macOS 10.14 or later, Linux, Chrome OS
	Auto Duplex Print			Yes		operating system c		
	Print Margins			Top/Bottom/Left/Right margin: 5 mm Top/Bottom/Left/Right margin: 10 mm (Envelope)		Other Features		Force Hold Print, Department ID, Secure Print
	Supported File Format for USB Direct Print		t Print	JPEG, PDF, TIFF, XPS		Available Software		Printer Driver, Toner Status
	Input Tray Capacity (Plain paper, 80 g/m²)	Standard	Cassette	250 sheets		Device Memory		2 GB
			Multi- Purpose	100 sheets		Display		5-Line LCD
			Tray			Power Requirements		AC 220 - 240 V, 50/60 Hz
		Optional	Paper Feeder	550 sheets		Power	Operation	600 W (max. 1 710 W)
		Maximum		2 550 sheets (Standard + 4 Paper Feeders)		Consumption*5 (approx.)	Standby	30 W
	Output Tray Capacity (Plain paper, 80 g/m²)		80 g/m²)	250 sheets			Sleep	1 W
		Cassette/Paper Feeder*3 (Optional)		A3, A4, A5, A6, B4, B5, B6, Ledger, Letter, Executive, Statement, Foolscap, Government Letter, Government Legal, Indian Legal,	GENERAL	Operating	Temperature	10 - 30°C
					B	Environment	Humidity	20% - 80% RH (no condensation)
Ş				Custom (min. 85 x 148 mm to max. 297 x 431.8 mm)		Monthly Duty Cycle*6		150 000 pages
PAPER HANDLING		Multi-Purpose Tray		A3, A4, A5, A6, B4, B5, B6, Ledger, Legal, Letter, Executive, Statement, Foolscap, Government Letter, Government Legal, Indian Legal, Index Card, Postcard, Envelope (COM10, Monarch, DL, C5), Custom (min. A4 x 120 mm to max. 297 x 1,320 mm)		Dimensions (W x D x H) (approx.)		499 x 525 x 340 mm
					;	Weight*7 (approx.)		30.2 kg
PAPER	Media Size					Toner Cartridge*8	Standard	Cartridge 077: 15 000 prints (Bundled: 3 000 prints)
							Low	Cartridge 077L: 7 000 prints
		2-Sided Printing		A3, A4, A5, B4, B5, Ledger, Legal, Letter, Executive, Foolscap, Government Letter, Government Legal, Custom (min. 148 x 148 mm to max. 297 x 431.8 mm)		Paper Feeder		Paper Feeder PF-L1 (550 sheets)
	Media Type			Plain Paper, Recycled Paper, Label, Postcard, Envelope		Plain Pedestal		Plain Pedestal BA1
	Cassette/Paper		Paper Feeder	60 - 163 g/m²	OPTIONAL			
	Media Weight	Multi-Purp	ose Tray	60 - 250 g/m²	DPT	Barcode Printing Kit Barcode Printing Kit-		Barcode Printing Kit-D1E
		2-Sided Printing		60 - 163 g/m²				

<sup>11</sup> Print speed is measured based on internal testing using A4/Letter size paper printed with 100% print ratio to original on one-sided paper. Internal testing involved continuously printing the same one page of content on plain paper. Print speed may vary depending on paper type, paper size or paper feeding direction.

<sup>+2</sup> First print out time is measured based on internal test procedure and may vary. When the printer is in the ready state, this is the time from receiving the print instruction from the controller to printing one sheet and finishing paper ejection.

\*3 Custom size for paper feeder: min. 85 x 148 mm to max. 297 x 431.8 mm; additional attachment may be required.

\*4 The latest drivers for Windows, Windows Server, macOS and Linux can be downloaded from the https://asia.canon/support website when available.

 $^{\ast \scriptscriptstyle 5}$  Power consumption is based on internal test procedure and measurement and may vary.

\*6 Monthly Duty Cycle value provides a means of comparison for product robustness in relation to other Canon laser printer devices, and does not refer to actual maximum image output per month.

\*7 Excluding toner cartridge.

\*8 Toner cartridge is in accordance with ISO/IEC 19752.



# CANON INDIA PVT. LTD.

Delighting You Always

7th Floor, Tower B, Building #5, DLF Epitome Building, DLF Phase III, Gurugram-122002 Ph.: 0124-4160000 | Fax: 0124-4160011 | Web: in.canon

DEALER'S STAMP

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weight and dimensions are approximates. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.