### imageCLASS MF752Cdw MF756Cx





# Vibrant Colours with Smart Innovation

The MF752Cdw and MF756Cx colour laser printers allow businesses to boost creativity and efficiency in the workplace with printing versatility. Increase productivity through fast print speeds with impressive visuals.



PAGES PAGES High-yield cartridges



MF752Cdw

(Print • Scan • Copy)

## Greater Efficiency and Performance



#### Enhanced Swift Quality Printing

Experience increased productivity as A4 documents are printed swiftly at a print speed of 33pages/min and up to 60pages/min for A5 documents.



#### Fast Duplex Scan

Optimise time by scanning 2-sided documents simultaneously with an impressive scan speed of 100 images/min (mono) / 80 images/min (colour). For added convenience, the Skip Blank Page function eliminates the need to remove blank pages after scanning.



#### Cloud Scanning and Printing

MF756Cx

(Print • Scan • Copy • Fax)

For ease of collaboration, connect to a third-party cloud storage application (Dropbox, Google Drive and Microsoft OneDrive) to print directly or store scanned documents.

### V<sup>2</sup>COLOUR

#### Vivid & Vibrant Printouts

V<sup>2</sup> Colour Technology delivers captivating vivid and vibrant colour prints that will leave an impactful impression.



Improve workflow efficiency and simplify routine tasks by utilising a suite of customisable functions. With Print File From Server, you can store frequentlyused documents within a local network and print when required.

# Intuitive And Convenient Design



### Easy Navigation With Clarity

Enjoy greater viewing flexibility and intuitive navigation with the 127 mm (5-inch) vari-angle colour touchscreen LCD display.



#### Customisable For Any Workflow

Simply drag and drop the applications to customise the home screen according to your office workflow.

#### **Easy Maintenance**

Experience hassle-free toner cartridge replacements with the all-in-one toner cartridge which incorporates the toner reservoir, photosensitive drum and cleaning unit in one body.

#### SPECIFICATIONS

| PRINT  |                 | MF752Cdw (3-in-1)   | MF756Cx (4-in-1)                     |  |
|--|-----------------|---|--------------------------------------|--|
| Printing Method                                |                 | Colour Laser Beam Printing  |                                      |  |
|  | A4              | 33 pages/min (Mono / Colour)  |                                      |  |
| Print Speed                                    | Letter          | 35 pages/min (Mono / Colour)  |                                      |  |
|  | 2-Sided         | 29 pages/min (Mono / Colour)  |                                      |  |
| Print Resolution                               |                 | 600 x 600 dpi   |                                      |  |
| Print Quality with Image Refinement Technology |                 | 1200 x 1200 dpi (equivalent)  |                                      |  |
| Warm-Up Time (From Powe                        | r On)           | 14 s or less  |                                      |  |
| First Print Out Time (FPOT)                    | A4              | 7.1 s (Mono / Colour)   |                                      |  |
| First Frint Out Time (FPOT)                    | Letter          | 7.0 s (Mono / Colour)   |                                      |  |
| Recovery Time (From Sleep Mode)                |                 | 5.3 s or less   |                                      |  |
| Print Language                                 |                 | UFR II, PCL 6   | UFR II, PCL 6, Adobe° PostScript® 3™ |  |
| Auto Duplex Print                              |                 |   | Yes                                  |  |
| Print Margins                                  |                 | Top/Bottom/Left/Right Margin: 5 mm<br>Top/Bottom/Left/Right Margin: 10 mm (Envelope)        |                                      |  |
| Supported File Format for USB Direct Print     |                 | JPEG, TIFF, PDF   |                                      |  |
| COPY   |                 |   |                                      |  |
| Or and the second                              | A4              | 33 pages/min (Mono / Colour)  |                                      |  |
| Copy Speed                                     | Letter          | 35 pages/min (Mono / Colour)  |                                      |  |
| Copy Resolution                                |                 | 600 x 600 dpi   |                                      |  |
| First Copy Time (FCOT)<br>ADF                  | A4              | 7.6 / 8.8 s (Mono / Colour)   |                                      |  |
|  | Letter          | 7.4 / 8.6 s (Mono / Colour)   |                                      |  |
| Maximum Number of Copies                       |                 | Up to 999 copies  |                                      |  |
| Reduce/Enlargement                             |                 | 25 - 400% in 1% increments  |                                      |  |
| Copy Features                                  |                 | Frame Erase, Collate, 2 on 1, 4 on 1, ID Card Copy, Passport Copy                           |                                      |  |
| SCAN   |                 |   |                                      |  |
|  | Optical         | Platen glass: up to 600 x 600 dpi, Feeder: up to 300 x 300 dpi                              |                                      |  |
| Scan Resolution                                | Driver Enhanced | Up to 9 600 x 9 600 dpi   |                                      |  |
| Scan Type                                      |                 | Colour Con  | tact Image Sensor                    |  |
|  | Platen Glass    | Up to 216.0 x 297 mm  |                                      |  |
| Maximum Scan Size                              | Feeder          | Up to 216.0 x 355.6 mm  |                                      |  |
| Scan Speed"                                    |                 | 1-Sided: 50 / 40 images/min (Mono / Colour)<br>2-Sided: 100 / 80 images/min (Mono / Colour) |                                      |  |
| Colour Depth                                   |                 | 24-bit  |                                      |  |
| Pull Scan                                      |                 | Yes, USB and Network  |                                      |  |
| Push Scan (Scan To PC) with                    | MF Scan Utility | Yes, USB and Network  |                                      |  |
| Scan To USB (via USB Host 2.0)                 |                 | Yes   |                                      |  |
| Scan To Cloud                                  |                 | MF Scan Utility, Cloud Apps (Application Library)   |                                      |  |
| Scan Driver Compatibility                      |                 | TV  | VAIN, WIA                            |  |
| SEND   |                 |   |                                      |  |
| SEND Method                                    |                 | SMB, Email, FTP   | SMB, Email, FTP, iFAX                |  |
| colour Mode                                    |                 | Full Colour, Grayscale, Monochrome  |                                      |  |
| Scan Resolution                                |                 | 300 x 600 dpi   |                                      |  |
| File Format                                    |                 | JPEG, TIFF, PDF, Compact PDF, PDF (OCR)   |                                      |  |

# Safeguard Against Security Vulnerability



The latest security protocol, TLS 1.3, encrypts communication data and protects

against spoofing and eavesdropping.



0

Prevent unauthorised system modifications with Verify System at Startup. The integrity of device firmware and applications will be checked during startup.

#### **SPECIFICATIONS**

| SPECIFICATIONS   |  |  |  |  |  |  |
|--|--|--|--|--|--|--|
| FAX  |  | MF752Cdw (3-in-1)  | MF756Cx (4-in-1)   |  |  |  |
| Modem Speed  |  |  | Up to 33.6 Kbps  |  |  |  |
| Fax Resolution   |  |  | Up to 408 x 392 dpi  |  |  |  |
| Compression Method   |  |  | MH, MR, MMR, JBIG  |  |  |  |
| Memory Capacity*2  |  |  | Up to 512 pages  |  |  |  |
| Favourite Dials (in address book)  |  |  | 19 dials   |  |  |  |
| Speed Dial (Coded dials)   |  |  | Up to 281 dials  |  |  |  |
| Speed Dial (Coded dials)<br>Group dials / Destinations   |  | -  | Max. 299 dials / Max. 299 destinations   |  |  |  |
| -  |  | - N/A  | Yes  |  |  |  |
| Duplex Fax (Transmission   | 1)   |  |  |  |  |  |
| Sequential Broadcast   |  |  | Max. 310 destinations  |  |  |  |
| Receive Mode   |  |  | Fax Only, Manual, Answering, Fax/Tel Auto Switch   |  |  |  |
| Memory Backup  |  |  | Permanent fax memory backup (backup with flash memory)   |  |  |  |
| Fax Features   |  |  | Fax Forwarding, Dual Access, Remote Reception, PC Fax (Transmission on<br>DRPD, ECM, Auto Redial, Fax Activity Reports, Fax Activity Result Reports<br>Fax Activity Management Reports<br>Approx. 2.6 s  |  |  |  |
| Transmission Time  |  | 1  |  |  |  |  |
| PAPER HANDLING   |  |  |  |  |  |  |
| Auto Document Feeder (A  | ADF)   | Duplex ADF: 50 sheets (80 g/m <sup>2</sup> )   |  |  |  |  |
|  |  | A4, B5, A5, A6, Letter, Legal, Statement, Business Card  |  |  |  |  |
| Available Paper Size for A   | NDF .  |  | o max. 216.0 x 355.6 mm)   |  |  |  |
|  | Standard Cassette  | 250  | sheets   |  |  |  |
| Paper Input  | Multi-Purpose Tray   |  | sheets   |  |  |  |
| (Based on 80 g/m <sup>2</sup> )  | Optional Paper Feeder  | 550 sheets   |  |  |  |  |
| Maximum Paper Input Ca   |  |  | sheets   |  |  |  |
| Paper Output   | ······   |  | sheets   |  |  |  |
|  | Standard Cassette  | A4, B5, A5, A6, Letter, Legal, Statement, Executive, Government Letter, Government Legal, Foolscap, Indian Legal,<br>Envelope (COMti0, Monarch, C5, DL), Custom (min. 98.0 x 148.0 mm to max. 216.0 x 356.0 mm)  |  |  |  |  |
| Paper Sizes  | Multi-Purpose Tray   | A4, B5, A5, A6, Letter, Legal, Statement, Executive, Government Letter, Government Legal, Foolscap, Indian Legal, Index Card,<br>Erwelope (COM10, Monarch, C5, DL), Custom (min. 76.0 x 127.0 mm to max. 216.0 x 356.0 mm)   |  |  |  |  |
|  | Optional Paper Feeder  | A4, B5, A5, A6, Letter, Legal, Statement, Executive, Government Letter, Government Legal, Foolscap, Indian Legal,<br>Custom (min. 100.0 x 148.0 mm to max. 216.0 x 356.0 mm)   |  |  |  |  |
| Available Paper Size for Auto Duplex Print   |  | A4, B5, A5, Letter, Legal, Executive, Foolscap, Indian Legal   |  |  |  |  |
| Paper Types  |  | Plain, Thick, Coated, Recycled, Colour, Label, Postcard, Envelope  |  |  |  |  |
|  | ADF  | 50 to  | 50 to 105 g/m <sup>2</sup>   |  |  |  |
| Paper Weight   | Standard Cassette /<br>Optional Paper Feeder   | 60 to 200 g/m²   |  |  |  |  |
|  | Multi-Purpose Tray   | 60 to 200 g/m <sup>2</sup>   |  |  |  |  |
| <b>CONNECTIVITY &amp; SOFT</b>   | WARE   |  |  |  |  |  |
| Stendard Interfaces  |  | USB 2.0 High Speed, 10Base-T/100Base-TX/1000Base-T   |  |  |  |  |
| Standard Interfaces  | Wireless   | Wi-Fi 802.11b/g/n (Infrastructure mode, WPS, Direct Connection)  |  |  |  |  |
|  | Print  | LPD, RAW, WSD-Print (IPv4, IPv6)   |  |  |  |  |
|  | Scan   | Email, SMB, WSD-Scan (IPv4, IPv6), FTP   |  |  |  |  |
| Network Protocol   | TCP/IP Application Services  | Bonjour (mDNS), HTTP, HTTPS, POP before SMTP (IPv4, I  | Pv6), DHCP, ARP+PING, Auto IP, WINS (IPv4), DHCPv6 (IPv6)  |  |  |  |
|  | Management   |  | /IPv3 (IPv4, IPv6)   |  |  |  |
|  | Wired  |  | SNMPv3, IEEE802.1x, IPSEC, TLS 1.3   |  |  |  |
| Network Security   | Wireless   | Infrastructure Mode: WEP (64/128 bit), WPA-PSK (TKIP/AES), WP  | A2-PSK (TKIP/AES), WPA-EAP (AES), WPA2-EAP (AES), IEEE8021x<br>ie: WPA2-PSK (AES)  |  |  |  |
| Other Features   |  |  | Print, Application Library   |  |  |  |
| Mobile Solution  |  |  | AirPrint <sup>®</sup> , Mopria <sup>®</sup> Print Service, Microsoft Universal Print   |  |  |  |
| Address Book   |  |  |  |  |  |  |
| Compatible Operating Sy  | etome <sup>13</sup>  |  | Server®, Mac® OS, Linux <sup>4</sup>   |  |  |  |
| Software Included  |  | Printer driver, Scanner driver, MF Scan Utility, Toner Status  | Printer driver, Fax driver, Scanner driver, MF Scan Utility, Toner Status  |  |  |  |
| GENERAL  |  | i ninter univer, ocaniner univer, IVIF ocan otility, Toher Status  |  |  |  |  |
| Device Memory  |  |  | GB   |  |  |  |
| Device memory<br>Display   |  |  | nch Touch Screen Display   |  |  |  |
| Diopiny  |  |  |  |  |  |  |
| Dimensions (W x D x H)   |  |  | 11 x 430 mm  |  |  |  |
| Weight   |  | 21.7 kg  | 22.0 kg  |  |  |  |
| Power Consumption  | Maximum (Operation)  | 1380 W or less   |  |  |  |  |
|  |  |  | 700 W  |  |  |  |
| Power Consumption  | Average (Operation)  | 70   |  |  |  |  |
| Power Consumption  | Average (Standby)  | 70   | 1.0 W  |  |  |  |
| Power Consumption  | Average (Standby)<br>Average (Sleep)   | 70<br>24<br>1.0 W (USB/  | 1.0 W<br>Nired/Wireless)   |  |  |  |
|  | Average (Standby)  | 70<br>24<br>1.0 W (USB/  | 1.0 W  |  |  |  |
| Power Consumption Operating Environment  | Average (Standby)<br>Average (Sleep)   | 77<br>24<br>1.0 W (USB/<br>10 - 10 -   | 1.0 W<br>Nired/Wireless)   |  |  |  |
| Operating Environment  | Average (Standby)<br>Average (Sleep)<br>Temperature  | 77<br>24<br>1.0 W (USB/<br>10 - 10-<br>20% - 80% RH  | I.O W<br>Nired/Wireless)<br>-30°C<br>(no condensation)   |  |  |  |
|  | Average (Standby)<br>Average (Sleep)<br>Temperature  | 77<br>24<br>1.0 W (USB/<br>10 W (USB/<br>10<br>20%-80% RH<br>AC 220 - 240 V (+/-1<br>Cartridge 069 BK. 2 100   | LO W<br>Wired/Wireless)<br>-30°C<br>(no condensation)<br>0%), 50/60 Hz (+/-2 Hz)<br>pages (bundled: 2 100 pages)   |  |  |  |
| Operating Environment  | Average (Standby)<br>Average (Sleep)<br>Temperature<br>Humidity<br>Standard                        | 7/<br>22<br>1.0 W (USB/<br>0<br>20%-80% RH<br>AC 220 - 240 V (+/-1<br>Cartridge 069 BK: 2100<br>Cartridge 069 CMY: 1900<br>Cartridge 069 CMY: 1900<br>Cartridge 06   | 1.0 W<br>Wired/Wireless)<br>-30°C<br>(no condensation)<br>0%), 50/60 Hz (+/-2 Hz)<br>pages (bundled: 1 200 pages)<br>) pages (bundled: 1 100 pages)<br>9H BK: 7 600 pages  |  |  |  |
| Operating Environment<br>Power Requirements<br>Toner Cartridge <sup>15</sup>   | Average (Standby)<br>Average (Sleep)<br>Temperature<br>Humidity                                    | 7/<br>22<br>1.0 W (USB/<br>1.0 W (USB/ | LO W           Wired/Wireless)           -30°C           (no condensation)           0%), 50/60 Hz (+/-2 Hz)           pages (bundled: 2 100 pages)           ) pages (bundled: 1 100 pages)           H BK-7 600 pages           H CMY: 5 500 pages |  |  |  |
| Operating Environment Power Requirements Toner Cartridge's Monthly Duty Cycle'e  | Average (Standby)       Average (Sleep)       Temperature       Humidity       Standard       High | 7/<br>22<br>1.0 W (USB/<br>1.0 W (USB/ | 1.0 W<br>Wired/Wireless)<br>-30°C<br>(no condensation)<br>0%), 50/60 Hz (+/-2 Hz)<br>pages (bundled: 1 200 pages)<br>) pages (bundled: 1 100 pages)<br>9H BK: 7 600 pages  |  |  |  |
| Operating Environment<br>Power Requirements<br>Toner Cartridge's<br>Monthly Duty Cycle'e<br>OPTIONAL ACCESSORI   | Average (Standby)       Average (Sleep)       Temperature       Humidity       Standard       High | 77<br>24<br>1.0 W (USB/<br>10 W (USB/<br>10 -<br>20% - 80% RH<br>AC 220 - 240 V (+/-1<br>Cartridge 069 GMY: 190<br>Cartridge 069 GMY: 190<br>Cartridge 069<br>Cartridge 069<br>Cartridge 069<br>Cartridge 069<br>50 00   | LO W<br>Wired/Wireless)<br>-30°C<br>(no condensation)<br>0%), 50/60 Hz (+/-2 Hz)<br>pages (bundled: 2 100 pages)<br>0 pages (bundled: 1100 pages)<br>0H BK-7 600 pages<br>H CMY: 5 500 pages<br>H CMY: 5 500 pages                                   |  |  |  |
| Operating Environment<br>Power Requirements<br>Toner Cartridge <sup>15</sup><br>Monthly Duty Cycle <sup>16</sup><br>OPTIONAL ACCESSORI<br>Paper Feeder | Average (Standby)       Average (Sleep)       Temperature       Humidity       Standard       High | 77<br>24<br>10 W (USB/<br>10 W (USB/<br>10<br>20% – 80% RH<br>AC 220 – 240 V (+/-1<br>Cartridge 069 BK. 2100<br>Cartridge 069 BK. 2100<br>Cartridge 069 BK. 2100<br>Cartridge 069<br>Cartridge 060<br>Cartridge 060<br>Cartridge 060<br>Cartridge 060<br>Cartridge 060<br>Cartridg   | LO W<br>Wired/Wireless)<br>-30°C<br>(no condensation)<br>0%), 50/60 Hz (+/-2 Hz)<br>pages (bundled: 2100 pages)<br>0 pages (bundled: 1100 pages)<br>0H BK-7 600 pages<br>H CMY: 5 500 pages<br>M CMY: 5 500 pages<br>F-K1 (550 sheets)               |  |  |  |
| Operating Environment<br>Power Requirements<br>Toner Cartridge <sup>15</sup><br>Monthly Duty Cycle <sup>16</sup><br>OPTIONAL ACCESSORI                 | Average (Standby)       Average (Sleep)       Temperature       Humidity       Standard       High | 77<br>24<br>1.0 W (USB/<br>10 W (USB/<br>10 -<br>20% - 80% RH<br>AC 220 - 240 V (+/-1<br>Cartridge 069 GMY: 190<br>Cartridge 069 GMY: 190<br>Cartridge 069<br>Cartridge 069<br>Cartridge 069<br>Cartridge 069<br>50 00   | LO W<br>Wired/Wireless)<br>-30°C<br>(no condensation)<br>0%), 50/60 Hz (+/-2 Hz)<br>pages (bundled: 2 100 pages)<br>0 pages (bundled: 1100 pages)<br>0H BK-7 600 pages<br>H CMY: 5 500 pages<br>H CMY: 5 500 pages                                   |  |  |  |

<sup>11</sup> Speed of scanning via the document feeder, A4 size, scan resolution 300 x 300 dpi.
 <sup>12</sup> Based on ITU-T #1 Chart (standard mode).
 <sup>13</sup> ScanGear is not available for Windows Server 2003/2008/2012.

<sup>15</sup> The latest drivers for Windows, Windows, Windows Server, Mac OS and Linux can be downloaded from the https://asia.canon website when available.
 <sup>15</sup> Toner cartridge yield is in accordance with ISO/IEC 19798.
 <sup>16</sup> Monthly Duty Cycle value provides a means of comparison for product robustness in relation to other Canon multi-function laser devices, and does not refer to actual maximum image output per month.

### Canon Delighting You Always

#### **CANON INDIA PVT. LTD.**

7th Floor, Tower B, Building #5, DLF Epitome Building, DLF Phase III, Gurugram-122002 Ph.: 0124-4160000 | Fax: 0124-4160011 | Web: in.canon

| DEAI | _ER'S | STA | MP |
|------|-------|-----|----|
|      |       |     |    |

This document is for information purpose only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.