

imagePROGRAF

TC Series

PRINT, COPY, SCAN.

ALL-IN-ONE DESKTOP LARGE FORMAT PRINTER



#TheArchitectsChoice







Roll Paper & Cut Sheet Support



Compact Width



280 ml (4x 70ml) Bundled Pigment Ink



High durability* against water



Minimal Margin Printing



Print, Copy & Scan

The imagePROGRAF TC Series provides exceptional versatility in creating high-quality CAD drawings, posters and large prints. Compact and easy to operate, experience greater productivity that boosts your workflow even in small workplaces with the ability to print from A6 to A1 sizes. Improve business efficiency through enhanced scanning and copying of original documents using the A4 flat-bed scanner.

COMPACT & EFFICIENT WITH EXCELLENT PRINT QUALITY

The TC series boasts a small footprint with a width of 609.6 mm (24 inches). The 4-colour pigment ink produces vivid red colours create stunning printouts that impress, and its ease of operation boosts efficiency and productivity.

COMPACT WIDTH

The 609.6 mm (24 in) width helps the TC series to easily fit into shelves, or be placed on desks within small offices while allowing for an optional printer stand and desktop basket.



MINIMAL MARGIN PRINTING

The TC series delivers high quality output on roll paper with minimal margins of approximately 0.5mm on the left and right sides, keeping it borderless on the top and bottom.

VERSATILE MEDIA HANDLING

Supports a wide range of paper sizes from A6 to A1-sized/24-inch width and various paper types like from postcards, envelopes, labels and office documents to CAD line drawings, posters and long banners.



AUTOMATIC SWITCHING ROLL PAPER / CUT SHEET

The TC series supports output prints of **up to A1-sized**/ **609.6 mm (24 in) width** roll paper alongside the easy loading of cut sheet media, while the Auto Sheet Feeder can cater for **100 A4* or 50 A3* sheets**.





Roll Paper

Cut Sheet

*Plain paper

Lines & text remain visible

after water spills

BUNDLED INK BOTTLES

The TC series comes with large bundled ink bottles with a **total capacity of 280 ml** (4 colours x 70 ml), instantly catering for any print needs.



HIGH IMAGE QUALITY

The TC series features all-colour pigment ink printing and delivers **vivid colour expression** in posters and flyers, especially in **red**. Printouts that are created **do not smudge easily** from water spills & highlighter marks, ensuring that they remain legible.

Effects of water spills* on prints



Printed with TC-21M


*Water droplets on the drawing 24 hours after it was printed on plain paper "Red Label 75g/m² (gsm)" and using Canon original ink.

MULTIPLE COPY FUNCTIONS

Enlargement copy, repeat copy, layout copy and image stitch copy functions are available on the TC-21M.

Enlargement Copy


A4 documents can be scanned and enlarged up to A1 or 609.6mm (24in) size on roll paper, or up to A3 on cut sheets to maximize the image automatically. The orientation of the image can be selected on the user panel.





Repeated Copy

Repeatedly copy an A4 document to fit the width of roll paper. Fitted to maximum roll width of A1/609.6 mm (24in).



Layout Copy*

Multiple original images can be copied in order into one continuous layout and fitted to the roll paper width. Fitted to maximum roll width of A1/609.6 mm (24in).



Maximum of 4 A4 original images can be copied

APPLICATIONS



SPECIFICATIONS

PRINTER		TC-21	TC-21M
Printer Type		4-Colour, 609	9.6 mm (24 inch)
Number of Nozzles		4 352 nozzles (BK: 1 280 nozzles, Other Colours: 1 024 nozzles each)	
Max. Print Resolution		2 400 x 1 200 dpi	
Nozzle Pitch		1 200 dpi x 2	
Line Accuracy ¹		± 0.1% or less	
	Sales Ink	70 ml x 4 (BK / C / M / Y)	
Ink Bottle Size	Bundle Starter Ink	70 ml x 4 (BK / C / M / Y)	
Ink Type		Pigment Ink	
	For Printer	Windows Printer Driver	
Windows Platform	For Scanner	-	Windows Scanner Driver, WIA Driver, Windows Scanner Utility, IJ Network Scanner Selector EX
MAC Platform	For Printer	Canon IJ Printer Driver	
WAC FIATIOTH	For Scanner	-	IJ Scan Utility Lite
Print Languages		SG Raster	SG Raster, PDF, JPEG
Print Solutions		ChromeOS, Canon PRINT Inkjet/SELPHY (iOS/Android), Canon Print Service, Free Layout Plus, PosterArtist Web, Direct Print Plus (PDF/JPEG), PIXUS/PIXMA Cloud Link	
Management Soluti	ons		ool, Quick Utility Toolbox, tant, Printer Update Utility
	USB A Port	-	USB Memory (Direct Print), JPEG/PDF*2 (Exif ver2.2/2.21/2.3)
	USB B Port	Hi-Speed USB, Full Speed (12 Mbit/sec), Hi-Speed (480 Mbit/sec), Bulk Transfer, Series B (4 pins)	
Interface (Built-in)	Network	IEEE 802.3 10base-T, IEEE 802.3u 100base-TX, SNMP HTTP, TCP/IP (IPv4/IPv6)	
	Wireless LAN	IEEE802.11 a/b/g/n/ac WPA-PSK (TKIP/AES) WPA2-PSK (TKIP/AES) WPA3-SAE(AES) WPA-EAP(AES) ³ WPA2-EAP(AES) ³ WPA3-EAP(AES) ³	
Memory		1 GB	
Display		LCD (6.7cm / 2.7 inch) (Touch Screen, Color, Tilt)	
OS Compatibility		Windows, Macintosh "Please visit https://asia.canon to confirm OS compatibility and to download the latest drivers.	
SCANNER			
Scanner Type			Flatbed (CIS Scanner)
			1 200 x 2 400 dpi
Optical Resolution	Grayscale		16bit/8bit
(DPI)*4	Colour	RGB 16bit/8bit	
Scanning Speed	Grayscale/ Monochrome	-	1.5 ms/line at 300 dpi
	Colour	1	3.5 ms/line at 300 dpi
Maxmum Documen	t Size	1	A4/LTR (216 x 297 mm)
PRINT SPEED'5		A1 SIZE	
Plain Paper	CAD Drawing	30 s (Draft) (Monochrome)	
MEDIA HANDLIN	G	TC-21	TC-21M
	Roll Paper	297 - 610 mm (A3 width to 609.6 mm (24 inch)	
Media Width	Cut Sheet	89 - 297 mm (A3, A4, Letter, A5, A6)	
Media Thickness	Roll Paper/ Cut Sheet	0.08 - 0.28 mm	
Printable Media Width	Roll Paper	297 - 610 mm	
	Cut Sheet	89 - 297 mm	
Printable	Roll Paper	203.2 mm - 4 m	
Media Length	Cut Sheet	127 - 1200 mm	
	- 31 0001	127 1200 11111	

Specifications are	subject to	change withou	it notice.
opoomoutions are	oubjoot to	onango mino	

- ^{*1} User adjustments required. Printing environment and media must match those used for the adjustments.

- Paper required: Plain paper and coated paper only.

 Pop required: Plain paper and coated paper only.

 Pop supports only files generated by TC Series and Canon IJ products.

 IEEE802.1X (EAP-TLS/EAP-TTLS/PEAP) supported.

 Optical resolution is based on the ISO 14473 standard and represents the maximum sampling rate for scanning documents.
- 5 A1 page portrait orientation, plain paper with fastest print mode setting. Print speed (time taken to print one page) does not include time required for data processing, data transfer and pre-printing operations.

Media Core Size		50.8 mm (2 inch) core		
Outside Diameter Roll Paper		110 mm or less		
	Roll Paper	1 Roll		
Media Feed	Cut Sheet	Automatic Switch Function (ASF)		
Delivery Direction		Face-up, Front side		
	Recommended Area (Roll Paper)	Top, Bottom, Left, Right: 5mm *Some photo modes - Top: 30 mm, Bottom: 30 mm		
Margins (Top, Bottom, Side)	Recommended Area (Cut Sheet)	Top, Bottom, Left, Right: 5mm		
	Printable Area (Roll Paper)	Top, Bottom, Left, Right: 5mm *Some photo modes - Top: 30 mm, Bottom: 30 mm		
	Printable Area (Roll Paper Minimal Margin Print ^{*6})	Top, Bottom: 0 mm, Left, Right: approx. 0.5 mm		
	Printable Area (Cut Sheet)	Top, Bottom, Left, Right: 5mm		
DIMENSIONS (W	x D x H) & WEIGHT ⁻⁷			
	Printer	1 120 x 726 x 406 mm Weight: 45 kg	1 120 x 726 x 406 mm Weight: 46 kg	
Packaged Dimensions	Stand + Basket (SD-24) (W x D x H)	1 058 x 826 x 270 mm Weight: 20kg		
	Desktop Basket (BU-06) (W x D x H)	798 x 301 x 111 mm Weight: 2.0 kg		
Printer Dimension	Printer	968 × 613 × 395 mm (ASF® Opened, OP® Opened) 968 × 553 × 395 mm (ASF® Opened, OP® Closed) 968 × 593 × 245 mm (ASF® Closed, OP® Opened) 968 × 533 × 245 mm (ASF® Closed, OP® Opened)		
	With Stand + Basket (SD-24) (W x D x H)	Weight' ¹⁰ : 32 kg Weight' ¹⁰ : 34 kg 968 × 868 × 1024 mm (ASF ¹⁸ , OP ⁹ , Basket Opened) 968 × 720 × 874 mm		
			, Basket Closed) Weight ^{*10} : 44 kg	
	With Desktop Basket (BU-06) (W x D x H)	968 × 845 × 1115"1 mm (ASF's, OP's, Basket Opened) 968 × 595 × 965"1 mm (ASF's, OP's, Basket Closed) Weight'10; 33 kg Weight'10; 33 kg Weight'10; 35 kg		
POWER & OPERA	TING REQUIREMENT	S		
Power Supply (Prin	ter)	AC 100 - 240 V (50 - 60 Hz)		
Power	Operation	Operation: Approx. 28 W, Sleep Mode: Approx. 1.7 W		
Consumption (Printer)	Sleep Mode	Approx. 2.3 W		
,	Power OFF	Approx. 0.07 W		
Recommended	Temperature	15 - 30 °C		
Environment	Humidity	10 - 80% RH (no dew condensation)		
	Power*12	Approx. 6.0 Bels		
Acoustics	Pressure*12	Approx. 41.5 dB(A), Standby 35 dB(A) or less		
OPTIONAL ACCESSORIES				
Roll Unit		-		
2/3" Roll Holder		-		
Printer Stand + Basket		SD-24		
Desktop Basket		BU-06		
CONSUMABLES				
Ink Bottle		PFI-050 (70 ml)		
Print Head		PF-08		
Maintenance Cartridge		MC-32		

- *6 Includes roll holder set.
- *7 Auto Sheet Feeder

- Operation Panel

 Weight includes print head, excluding ink.

 Height above which desktop basket's cloth does not touch the floor when opening the desktop basket.
- 11 Acoustic power and pressure are measured using ISO 7779 standard.

CANON INDIA PVT. LTD.

7th Floor, Tower B, Building #5, DLF Epitome Building, DLF Phase III, Gurugram-122002 Ph.: 0124-4160000 | Fax: 0124-4160011 | Web: in.canon

Part Code: 9700W269

DEALER'S STAMP

This document is for information purposes only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.

© Canon India Pvt. Ltd. 2025. All rights reserved.

Canon India complies with the E-Waste (Management) Rules, 2022 and its amendments.

Please return end-of-life product for environmentally safe disposal. For details visit www.canon.co.in/recycle

This document is for information purpose only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and products names are trademarks and/or registered trademarks of their respective owners.

Warnings: Unauthorized recording of copyrighted materials may infringe on the rights of copyright owners and be contrary to copyright laws.

E-Waste Rules:
Canon India complies with the E-Waste (Management) Rules, 2022 and its amendments. This product is in accordance with the rule 16 pertaining to the Reduction in the use of hazardous substances (ROHS). Once this product reaches to end of life, this product should not be disposed of with your regular household waste.

