

**imageRUNNER  
ADVANCE DX | C359i**

## A4 multi-function device delivers productivity while remaining compact

The imageRUNNER ADVANCE DX C359i delivers outstanding colour output while maintaining small footprint. Paired with comprehensive security capabilities, the device will seamlessly integrate into any modern workplace.

### WORKFLOW EFFICIENCY

- Intuitive touchscreen provides users with smartphone-like usability, making navigation a breeze.
- Intelligent feeder allows effortless, rapid scanning with features like multi-sheet feed detection and skip blank originals.
- My ADVANCE enables a unique, personal experience tailored to meet each user's workflow needs. Settings, such as display language, initial log-in screen, and accessibility options, can be synchronised across multiple devices for consistency.
- Canon's MEAP platform provides process optimisation, by integrating with a range of powerful document, capture and output management solutions.
- Scalable support for mobile where users can connect directly to the device with Direct Access Point. Capture, scan or print documents easily with the Canon Print Business app.

### COST MANAGEMENT

- The ability to apply print policies, monitor output, and restrict usage by user helps reduce unnecessary printing, resulting in lower total document cost.
- Tight integration with output management solutions, such as uniFLOW, provides the ability to carry out detailed tracking, reporting, and cost analysis.
- Quality and reliability, combined with remote diagnostics and assistance, can help reduce costs by minimising downtime and time spent by IT.
- Consistent user operation combined with remote and centralised fleet management can help simplify IT management of devices and entire fleets.

## QUALITY AND RELIABILITY

- V<sup>2</sup> (Vivid & Vibrant) imaging technology ensures high quality printouts that impress time after time.
- Supreme transferability of toner and stable reproduction of colours onto a wide range of media, even at large volumes.
- State-of-the-art imaging technologies and toner allow for consistently striking images with 1 200 dpi print resolution.
- Canon's device management tools give you a centralised point of control across your entire fleet, upgrade devices remotely, check device and consumables status and capture meter readings.
- Standard PCL and Adobe PostScript print driver allows seamless integration with enterprise applications.
- Remote diagnostics allow timely, accurate and effective resolution.
- Intuitive user maintenance videos and status notifications available to help achieve maximum uptime and keep supplies replenished.

## SUSTAINABILITY

- CS Toner (consistently stable) provides print quality even for high volume print jobs.
- Minimise paper waste by holding jobs at the device with Force Hold Print. Choose to preview your print jobs or even change print settings at the device to achieve the desired results at the first time of printing.
- Consumes as little as 0.8W in sleep mode.

## SECURITY

- Control who has access to the device with different authentication methods such as picture login, department ID, user authentication and card access.
- Ensure information privacy and security across your network with IPsec, port filtering capabilities, and SSL technology.
- Enhance document confidentiality with encrypted secure print, secure print, secure watermark, encrypted PDF and device signature PDF.
- System verification at startup and McAfee® Embedded Control ensures device security, protecting against malware and tampering of firmware.
- Integrate with third-party solutions for complete monitoring protection.

# MACHINE SPECIFICATION

## MAIN UNIT

### Type

A4 Colour Laser Multifunctional

### Core Function

Print, Copy, Scan, Send, Store and Optional Fax

### Processor

Canon Dual Custom Processor (Shared)

### Control Panel

25.654 cm (10.1 in) TFT LCD WSVGA Colour Touch panel

### Memory

RAM Main CPU: 2GB  
Image Processing CPU: 1GB + 0.5GB

### Storage

(SSD) 256GB

### Interface Connection

#### Network

Standard : 1000Base-T/100Base-TX/10Base-T  
Optional : Wireless LAN (IEEE 802.11 b/g/n)

#### Others

Standard : USB 2.0 x1 (Host), USB 3.0 x1 (Host),  
USB 2.0 x1 (Device)

Optional : Serial Interface, Copy Control Interface

### Paper Supply Capacity (A4, 80g/m<sup>2</sup> (gsm))

Standard : 650 sheets (1 x 550-sheet cassettes,  
1 x 100-sheets multi-purpose tray)  
Maximum : 2 300 sheets  
(with Cassette Feeding Unit-AK1)

### Paper Output Capacity (A4, 80g/m<sup>2</sup> (gsm))

Standard : 250 Sheets  
Maximum : 500 Sheets (with Staple Finisher-Z1)

### Finishing Capabilities

Collate, Group, Offset, Staple

\* Finishing capabilities vary depending on the options connected

### Supported Media Types

#### Multi-purpose tray:

Thin, Plain, Heavy, Recycled, Colour, Transparency,  
Envelope, Pre-punched, Bond, Postcard, Labels

#### Paper Cassette:

Thin, Plain, Heavy, Recycled, Colour, Pre-punched, Bond,  
Envelope

### Supported Media Sizes

#### Multi-purpose tray:

Standard size : A4, A5, A5R, A6, B5,  
Custom size : 98.0 x 148.0 mm to 216.0 x 355.6 mm  
Envelopes : COM10 No.10, Monarch, DL, ISO-C5  
Custom size : 98.0 x 148.0 mm to 216.0 x 355.6 mm

#### Paper Cassette:

Standard size : A4, A5, A5R, A6, B5  
Custom Size : 98.0 x 190.5 mm to 216.0 x 355.6 mm  
Envelopes : COM10 No.10, Monarch, DL, ISO-C5

### Supported Media Weights

Multi-purpose tray : 60 to 220g/m<sup>2</sup> (gsm)  
Paper Cassette : 60 to 163g/m<sup>2</sup> (gsm)  
Duplex : 60 to 163g/m<sup>2</sup> (gsm)

### Warm-up Time

Quick Startup Mode : 4 s or Less<sup>\*1</sup>  
From Sleep Mode : 10 s or Less  
From Power On : 10 s or Less<sup>\*2</sup>

\*1 Time from device power-on to when the copy icon appears and is enabled to operate on the touch panel display.

\*2 Time from device power-on, until copy ready (not print reservation)

**Dimensions (W x D x H)** 519.0 mm x 658.0 mm x 638.0 mm

### Installation Space (W x D)

Basic: 852.0 x 908.0 mm (with Multi-purpose tray extended + paper cassette opened)  
Fully Configured: 1 407.0 x 908.0 mm (with Staple Finisher-Z1 + Multi-purpose tray extended + paper cassette opened)

**Weight** Approx. 49kg including toner

## Printing Specifications

### Print Speed (BW and CL, 1 sided)

iR-ADV DX C3591 : up to 35 pages/min (A4)  
up to 26 pages/min (A5R)  
up to 61 pages/min (A5)  
up to 23 pages/min (A6)

**Print Resolution (dpi)** 1200 x 600

### Page Description Languages

Standard: UFR II, PCL6, Adobe PostScript 3

### Direct Print

Supported file types: TIFF, JPEG, PDF, EPS and XPS

### Printing from mobile and cloud applications

AirPrint, Mopria, Canon PRINT Business, uniFLOW Online and Universal Print

### Fonts

PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts,  
Andalé Mono WT/J/K/S/T<sup>\*1</sup> (Japanese, Korean,  
Simplified and Traditional Chinese), Barcode fonts<sup>\*2</sup>  
PS fonts: 136 Roman

\*1 Requires optional PCL INTERNATIONAL FONT SET-A1

\*2 Requires optional BARCODE PRINTING KIT-D1

### Operating System

UFR II: Windows@10/Windows@11/Windows@Server2012/  
Windows@Server2012 R2/Windows@Server2016/  
Windows@Server2019/Windows@Server2022/  
macOS (10.13 or later)

PCL: Windows@10/Windows@11/Windows@Server2012/  
Windows@Server2012 R2/Windows@Server2016/  
Windows@Server2019/Windows@Server2022

PS: Windows@10/Windows@11/Windows@Server2012/  
Windows@Server2012 R2/Windows@Server2016/  
Windows@Server2019/Windows@Server2022/  
macOS (10.13 or later)

PPD: Windows@ 10/11, Mac OS X(10.13 or later)

## Copy Specifications

### Copy Speed (BW and CL, 1 sided)

iR-ADV DX C3591 : up to 35 pages/min (A4)  
up to 26 pages/min (A5R)  
up to 61 pages/min (A5)  
up to 23 pages/min (A6)

**First-Copy-Out Time** Approx. 5.1/6.9 s or less  
(A4, BW/CL)

**Copy Resolution (dpi)** 600 x 600, 300 x 600

**Multiple Copies** Up to 999 sheets

**Copy Density** Automatic or Manual (9 Levels)

### Magnification

Variable zoom: 25% to 400% (1% Increments)  
Preset reduction/enlargement: 25%, 50%, 70%, 81%, 86%,  
100% (1:1), 115%, 122%, 141%, 200%, 400%

## Scan Specifications

### Standard Type

Single-pass Duplexing Automatic Document Feeder\*  
[2-sided to 2-sided (Automatic)]

\* Detect Feeder Multi Sheet Feed is supported.

### Document Feeder Paper Capacity (80g/m<sup>2</sup> (gsm))

Up to 100 Sheets

### Acceptable originals and weights

Platen: Sheet, Book and 3-Dimensional Objects

Document Feeder media weights:

1-sided scanning: 42 to 128g/m<sup>2</sup> (gsm) (BW), 64 to 128g/m<sup>2</sup> (gsm) (CL)

2-sided scanning: 50 to 128g/m<sup>2</sup> (gsm) (BW), 64 to 128g/m<sup>2</sup> (gsm) (CL)

Note: Business card: 80 to 220g/m<sup>2</sup> (gsm)

Originals with width narrower than A6: 50 to 128g/m<sup>2</sup> (gsm)  
(except business card)

## Supported Media Sizes

Platen scanning size: up to 216.0 x 355.6 mm  
Document Feeder media size: A4, A5R, A6, B5  
Custom size: 48.0 x 128.0 mm to 216.0 x 355.6 mm  
Business card: 48.0 x 85.0 mm to 55.0 x 91.0 mm

## Scan Speed (A4, BW and CL)

Send (300 x 300 dpi): Automatic Colour Select "OFF":  
1-sided Scanning : 95 images/min,  
2-sided Scanning : 190 images/min  
Automatic Colour Select "ON":  
1-sided Scanning : 50 images/min  
2-sided Scanning : 100 images/min

Copy: Scan Speed priority (300 x 600 dpi):  
1-sided Scanning : 50 images/min  
2-sided Scanning : 100 images/min  
Image Quality priority (600 x 600 dpi):  
1-sided Scanning : 30 images/min  
2-sided Scanning : 50 images/min

## Scan Resolution (dpi)

Scan for Copy : 600 x 600  
Scan for Send : (Push) 600 x 600 (SMB/FTP/WebDAV/  
IFAX), (Pull) 600 x 600  
Scan for Fax : 600 x 600

## Pull Scan Spec

Colour Network ScanGear2. For both TWAIN and WIA  
Supported OS: Windows@10/Windows@11/  
Windows@Server2012/Windows@Server2012 R2  
/Windows@Server2016/Windows@Server2019/  
Windows@Server2022

## Send Specifications

### Destination

Standard: E-mail/Internet FAX (SMTP), FTP, SMB,  
WebDAV, Mail Box  
Optional: Super G3 FAX, IP Fax

### Address Book

LDAP (2 000)/Local (1 600)/One-touch (200)

### Send Resolution (dpi)

Push : up to 600 x 600  
Pull : up to 600 x 600

### Communication Protocol

File : FTP (TCP/IP), SMB 3.1.1 (TCP/IP), WebDAV  
E-mail/I-Fax : SMTP, POP3

### File Format

Standard: TIFF, JPEG, PDF (Compact, Searchable, Apply  
policy, Optimize for Web, PDF A/1-b, Trace &  
Smooth, Encrypted, Device Signature, User  
Signature), XPS (Compact, Searchable, Device  
Signature, User Signature), Office Open XML  
(PowerPoint, Word)

## Fax Specifications

### Maximum Number of Connection Lines 1

Modem Speed Super G3 : 33.6 kbps  
G3 : 14.4 kbps

Compression Method MH, MR, MMR, JBIG

Resolution (dpi) 400x400 (Ultra Fine),  
200x400 (Super Fine),  
200x200 (Fine),  
200x100 (Normal)

### Sending/Receiving Size

Sending : A4, A5\*, A6\*, B5\*  
Receiving : A4, A5, B5

\* Sent as A4

FAX Memory Up to 30 000 pages (2 000 jobs)

Speed Dials Max. 200

Group Dials/Destinations Max. 199 dials

Sequential Broadcast Max. 256 addresses

Memory Backup Yes

## Store Specifications

### Mail Box (Number supported)

100 User Inboxes, 1 Memory RX Inbox,  
50 Confidential Fax Inboxes  
Maximum 10 000 Pages (2 000 jobs) Stored

### Advanced Box

Communication Protocol: SMB or WebDAV  
Supported Client PC: Windows® 10/11  
Concurrent Connections (Max.): SMB: 64, WebDAV: 3

Advanced Box available disc space  
Approx. 16GB (Standard HDD)

## Security Specifications

### Authentication and Access Control

User Authentication: Picture Login, Picture and PIN Login,  
Card Login, Username and Password Login, Function Level  
Login, Mobile Login)  
Department ID Authentication: Department ID and PIN  
Login, Function Level Login  
uniFLOW Online Express: PIN Login, Picture Login, Picture  
and PIN Login, Card Login, Card and PIN Login, Username  
and Password Login, Department ID and PIN Login,  
Function Level Login  
Access Management System: Access Control

### Document Security

Print Security: Secure Print, Encrypted Secure Print, Forced  
Hold Printing, uniFLOW Secure Print\*  
Receive Data Security: Confidential Fax Inbox Forwarding  
Received Documents Automatically  
Scan Security: Encrypted PDF, Device Signature PDF/  
XPS, User Signature PDF/XPS, Adobe LiveCycle Rights  
Management ES2.5 Integration  
BOX Security: Mail Box Password Protected, Advanced Box  
Access Control  
Send Data Security: Setting for requesting password input  
per transmission, Restricted E-mail/File send functions,  
Confirming FAX number, Allow/Restrict Fax Driver  
Transmissions, Allow/Restrict Sending from History, S/MIME  
Support  
Document Tracking: Secure Watermark  
\*Requires uniFLOW Online/uniFLOW

### Network Security

TLS 1.3, IPsec, IEEE802.1X authentication, SNMP V3.0,  
Firewall Functionality (IP/MAC Address Filtering), Dual  
Network Support (Wired LAN/Wireless LAN, Wired LAN/  
Wired LAN), Disabling Unused Functions (Enabling/  
Disabling Protocols/Applications, Enabling/Disabling  
Remote UI, Enabling/Disabling USB Interface), G3 FAX  
separation from LAN, USB Port separation from LAN,  
Prohibit the execution of files stored in the Advanced Box in the  
MFP, Scan and Send -Virus Concerns for E-mail Reception

### Device Security

Protecting SSD Data (SSD Data Encryption (FIPS140-2  
Validated), SSD Data Overwrite Erase, SSD Lock), Standard  
SSD Initialize, Trusted Platform Module (TPM), Job Log  
Conceal Function, Checking MFP Software Integrity  
(Verify System at Startup, Runtime Intrusion Detection),  
Common Criteria Certification (IEEEE2600.2/HCD-PP)

### Device Management and Auditing

Administrator Password, Digital Certificate And Key  
Management, Audit Log, Cooperating with External  
Security Audit System (Security Information and Event  
Management), Image Data Logging, Security Policy Setting

## Environment Specifications

### Operating Environment

Temperature: 10 to 30 °C  
Humidity : 20 to 80 % RH (Relative Humidity)

### Power Requirements

Power Source: 220-240 V, 50/60 Hz, 3.9 A

### Power Consumption

Maximum : 1 500 W  
Sleep mode : Approx. 0.8 W\*

\* 0.8W sleep mode is not available in all circumstances due to  
certain settings.

## Software and Printer Management

### Tracking and reporting

uniFLOW Online Express

### Remote Management Tools

iW Enterprise Management Console  
eMaintenance  
Content Delivery System

### Scanning Software

Color Network ScanGear 2

### Optimisation Tools

Canon Driver Configuration Tool

### Platform

MEAP (Multifunctional Embedded Application Platform)

### Document Publishing

IW DESKTOP

## Paper Supply Options

### Cassette Module-AE1

Paper Capacity : 550 Sheets(80g/m<sup>2</sup> (gsm))  
Paper Type : Thin, Plain, Heavy, Colour, Recycled,  
Pre-punched, Bond  
Paper Size : A4, A5R, B5  
Custom Size : 98.0 x 190.5 mm to 216.0 x 355.6mm  
Paper Weight : 60 to 163g/m<sup>2</sup> (gsm)  
Power Source : From the Main Unit  
Dimensions : 511.0 mm x 508.0 mm x 159.0 mm  
(W x D x H) (attached to the main unit)  
Weight : Approx. 10 kg

### Cassette Feeding Unit-AJ1

Paper Capacity : 550 Sheets(80g/m<sup>2</sup> (gsm))  
Paper Type : Thin, Plain, Heavy, Colour, Recycled,  
Pre-punched, Bond  
Paper Size : A4, A5R, B5  
Custom Size : 98.0 x 190.5 mm to 216.0 x 355.6mm  
Paper Weight : 60 to 163g/m<sup>2</sup> (gsm)  
Power Source : From the Main Unit  
Dimensions : 511.0 mm x 508.0 mm x 425.0 mm  
(W x D x H) (attached to the main unit)  
Weight : Approx. 16 kg

### Cassette Feeding Unit-AK1

Paper Capacity : 550 Sheets (80g/m<sup>2</sup> (gsm)) x 3 cassettes  
Paper Type : Thin, Plain, Heavy, Color, Recycled,  
Pre-punched, Bond  
Paper Size : A4, A5R, B5  
Custom Size : 98.0 x 190.5 mm to 216.0 x 355.6mm  
Paper Weight : 60 to 163g/m<sup>2</sup> (gsm)  
Power Source : From the Main Unit  
Dimensions : 511.0 mm x 508.0 mm x 425.0 mm  
(W x D x H) (attached to the main unit)  
Weight : Approx. 19 kg

## Output Options\*

### Staple Finisher-Z1

Tray Capacity(80gsm): A4, A5, A5R, A6, B5 (500 Sheets)  
Paper Weight : 60 to 220g/m<sup>2</sup> (gsm)  
Staple Position : Corner  
Staple Capacity (A4, B5): 30 Sheets (60 to 105g/m<sup>2</sup> (gsm))  
Power Source : From the Main Unit  
Dimensions : 555.0 x 459.0 x 301.0 mm (Unit size)  
(W x D x H)  
Weight : Approx. 14 kg

\* Paper capacity may vary with different paper type/size.

## System and Controller Options

### Print Accessories

PCL INTERNATIONAL FONT SET-A1  
PCL ASIAN FONT SET-A1

### Barcode Printing

BARCODE PRINTING KIT-D1

### FAX Accessories

SUPER G3 FAX BOARD-AT1  
REMOTE FAX KIT-A1  
IP FAX EXPANSION KIT-B1

### Interface Accessories

WIRELESS LAN BOARD-D1  
COPY CONTROL INTERFACE KIT-A1  
SERIAL INTERFACE KIT-K3

## Other Options

### Accessibility Accessories

ADF ACCESS HANDLE-A1

### Consumables

STAPLE-P1


For full specifications, please refer to the specification  
table on your local Canon web site.

# MAIN CONFIGURATION OPTIONS





**STAPLE FINISHER - Z1**

- 1-tray, 500 -sheet capacity
- Corner stapling up to 30 sheets (80g/m<sup>2</sup> gsm)




**CASSETTE FEEDING UNIT-AJ1**

- Supports up to A4
- Media weight 60–163g/m<sup>2</sup> (gsm)
- 550 sheets (80g/m<sup>2</sup> (gsm)
- Floor standing



**CASSETTE FEEDING UNIT-AK1**

- Supports up to A4
- Media weight 60–163g/m<sup>2</sup> (gsm)
- 3 x 550 sheets (80g/m<sup>2</sup> (gsm)
- Floor standing



**CASSETTE MODULE-AE1**

- Supports up to A4
- Media weight 60–163g/m<sup>2</sup> (gsm)
- 550 sheets (80g/m<sup>2</sup> (gsm)
- Desktop



Adobe PostScript

Partner / Dealer Stamp

To arrange for a demonstration, simply contact our office below.

**CANON INDIA PVT. LTD.**

7<sup>th</sup> Floor, Tower B, Building #5, DLF Epitome Building, DLF Phase III, Gurugram-122002  
Ph.: 0124-4160000 | Fax: 0124-4160011 | Web: in.canon

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weights and dimensions are approximates. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.

Canon, imageRUNNER ADVANCE, MEAP, eMaintenance, iW and Business Can Be Simple are trademarks of Canon Inc. and/or its affiliates. "MEAP" is a trademark of CANON Inc., referring to an "application platform" for Canon multifunction and single function printers. Other names may be the trademarks of their respective owners. uniFLOW is an independent party software distributed by Canon Singapore Pte Ltd.

Adobe, LiveCycle, PostScript, and the PostScript logo are either registered trademarks or trademarks of Adobe in the United States and/or other countries.

2023 Canon India Pvt. Ltd.  
All rights reserved. Printed in India.