

plotWAVE T30/T35 Printer with Scanner Express IV Scanning Unit

Carrier

EASY SECURE AND INTELLIGENT

10

LARGE FORMAT TECHNICAL DOCUMENT MANAGEMENT SYSTEM

Patented Radiant Fusing Technology

True Resolution of 600 x 1 200 dpi with Pico Printing Virtually No Warm-up Time

Up to 914.4 mm (36in) Media Width and 2-roll capacity Perfect for Monochrome CAD/GIS

> Ergonomic Single Footprint Design

PRODUCTIVE EASE OF USE FOR THE YEARS AHEAD plotWAVE T30/35

Easy, Secure and Intelligent

For complex wide format print jobs, it is important that your printer produces impressive results every time. The plotWAVE Series makes printing easy with its intuitive user interface. Intelligent automation utilizes the power under the hood and tunes it to high performance. Top-notch security features safeguard your data, not only today, but also in the future. With its small footprint, ergonomic construction and clean, closed toner system, the plotWAVE Series is an excellent companion in busy office environments.

Complex Jobs and Document Sets Made Easy

With ClearConnect, even the most complex jobs and document sets become easy to print. Drag and drop files for great results. Accurate, live print previews enable users to check the effect of their print settings immediately. This gives peace of mind and avoids costly, time-wasting misprints. Standardize your workflow and efficiently repeat jobs with easy-to-create specialized media and scan templates.



True "Green Button" Printing

The highly productive plotWAVE T-series is designed to help users to save time and speed up the design process. Even for first-time users, the intuitive interface reduces the learning curve to an absolute minimum and helps prevent misprints or delays. Just push the green button! Operation is intuitive—even at first glance—and is built on easy-to-use drag-and-drop principles. You can submit files directly from your web browser and print directly from your compatible applications with an intuitive set of drivers.

Print From Anywhere? Easy!

Printing from many locations and sources is supported by the plotWAVE Series. With Publisher Mobile, you can preview and print files from your mobile phone or tablet. With Publisher Express, you can submit print files directly from the web. With Driver Select, the wide format printer driver for Windows reduces errors and gives you first-time-right results with its clear and easy-to-use functionalities. With Driver Express, you can print PostScript files from Mac and Windows.



SECURITY FEATURES FOR THE YEARS AHEAD plotWAVE T30/35



Designed with IT Security Features in Mind

Your confidential and restricted files can be shielded from unwelcome eves with many layers of security measures, such as credentials. LDAP domain user authentication, and password-protected print files. You can set a job-specific password or code to help protect print files with sensitive information. This can help prevent accidental printing by unauthorized users, so prints don't end up in the wrong hands or the paper bin. The and pre-installed network print management software adds optional additional IT security features, with options such as access card user authentication.



Security Features help Protect Your Data

Your data is protected in all phases of the print process. When the data is in transit, it is protected by secured, encrypted protocols. When at rest, your data is securely encrypted.

Since a printer is generally not used as a long-term data storage solution, deletion is made secure by data shredding and proper deleting protocols. There is also the option to remove the hard disk when the printer is decommissioned. Robust user authentication provides document security for users and activity control for budget managers. Hack prevention guards against malicious intrusion. All these security measures have been built for the long term: with software support, security updates and remote service.

Sustainable Environment

The plotWAVE series is a good office companion. With its low ozone emissions, low noise levels and low heat emission, it is perfect to place in office environments. The toner system is completely closed, so no unhealthy fumes can be inhaled.

Secure Your Productivity, Now and in the Future

The plotWAVE Series is built to withstand intensive use and safeguard your productivity, not just today, but for a long time into the future. The POWERsync Controller is based on the latest Windows 10 IoT OS, for long-term support.

INTELLIGENT AUTOMATION FOR THE YEARS AHEAD plotWAVE T30/35



Powerful, Intelligent Automation Features

Great way to be productive is to automate things. Radiant Fusing adjusts the temperature of the system to suit the media, helping to limit bad print results. Pico Printing automatically includes extra dots for impressive print quality. The powerful POWERsync+ controller is designed to help save you time by allowing scanning or copying while you're printing. The smart media handling features, such as media width detection, automatic remaining media detection, and automated roll switching, help you produce many impressive prints with minimal intervention and misprints.

Neat Document Delivery

The plotWAVE Series saves time with its neat document delivery options. Depending on your needs, you can easily collect your prints from the top delivery tray. The top delivery tray is positioned at an ergonomic height, and plots are neatly collated and stacked in the tray.

Consistent and Highly Productive

With virtually no warm-up time, the plotWAVE Series saves time and cuts energy costs. From sleep mode to print in hand in just 40 seconds. In addition, it reaches print speeds of up to 6 A1 or D-size prints per minute, or up to 360 A1 sheets per hour, unattended. With up to 2-roll media capacity, it provides the application range to print a variety of jobs in-house. This includes FSC paper, recycled paper and many other media types. The sheet feeding can be done manually one by one.



STREAMLINED WORKFLOW FOR THE YEARS AHEAD

We're not only one of the market leaders in high-performance printers, we're also a well-known developer of controllers and workflow software that gives architects, designers, and engineers the tools they need to do the job.



POWERsync⁺

IT Security Features

ClearConnect User Panel

Publisher Express

Publisher Mobile

Produce high-quality output with high productivity using our intuitive, easy-to-use interface.

Help protect your valuable information in all phases of the print process.

Print, copy, and scan with the multi-touch user panel, just as easy as using a tablet.

Submit your print jobs conveniently via the

Submit print jobs via your mobile phone app

web, independent of your web browser.







PRISMA Tech Suite

Create breathtaking applications while staying in control of your printer with powerful workflow solutions that are designed to help you with your day-to-day print operations.



PRISMAproduce Tech Compose, manage, and submit

complex sets of documents from your web browser to one or more printers at a time.3



PRISMAlytics Dashboard

Get comprehensive overviews to help monitor and maximize the production of your print operations with this secure cloudbased management information tool⁴








Driver Select

isher Express





panel, just as easy as using a tablet. application with our easy-to-use printer drivers.



PRISMAlytics Accounting Capture data for cost charging and usage monitoring with this cloud-based reporting tool.4

TECHNOLOGY

Imaging Technology

Fusing Technology

Automated Functions

Toner

STANDARD SYSTEM CONFIGURATION

2 Roll Printing System

Stacking Systems Multi-touch User Interface

Roll Media Switching

Earthquake Provision

Workflow Software

OPTIONAL SYSTEM CONFIGURATION

Removable Hard Disk

Speed (Print and Copy)

First Print Out Time

QUALITY

Print Resolution

Minimum Line Width (ISO/IEC 13660:2001E)

SIZE AND WEIGHT

Main Engine Size (WxDxH)

Main Engine Weight

MEDIA HANDLING

Media Capacity

Media Cutting Media Roll Size Media Size Cut Sheet Media Weight Roll Length and Width Roll Core Diameter Minimum Printed Length

Roll Media Type

Automatic Roll Media Handling

CONTROLLER

Description
Processor
Memory
Video
Hard disk
ТРМ

Client Operating System Support

Interface

Page Description Language

Printing Protocol

Electrophotography (LED) with Organic Photoconductor (OPC), Clean Toner Refill System, Virtually No Ozone Emission

 Radiant Fusing Technology with instant warm-up, contactless fusing, low power consumption (heating on demand)

 • Automated print language recognition
 • Automated media saving function
 • Auto media selection

Automated media saving function
 Pico Printing, intelligent print optimization
 Automated media saving function
Black toner

Productive wide format monochrome printer with ClearConnect multi-touch user panel Integrated Top Delivery Tray, up to 100 sheets capacity

ClearConnect multi-touch user interface: Smart Inbox, SmartAccess, Printer Status and Live Preview

Fully automated roll media switch to guide the media to the top delivery tray or back output depending on the user application

Secure the printer from moving or tilting during an earthquake. This provision enables the user to secure the printer to a sturdy element of the building (excluding cable/chain and mounting material)

ClearConnect Print Software Suite: Printer Driver Select for Microsoft Windows, Driver Express for Adobe PostScript 3, Publisher Select 3 for Microsoft Windows, Publisher Express for Web Browsers, Publisher Mobile for IOS and Android

For secure environments, hard disk can be removed from the printer system to secure data integrity

plotWAVE T30: 4 D/A1-sizes per minute, 2 E/A0 sizes per minute plotWAVE T35: 6 D/A1-sizes per minute, 3 E/A0 sizes per minute - D size (34 x 22 in) / A1 size (841 x 594 mm), E size (44 x 34 in) /A0 size (1189 x 841 mm)

<40 seconds (A1 landscape print made from the smart inbox, on 64 g/m² media, back output, lines and text mode)

600 x 1 200 dpi

0.06 mm

Compact design: 1560 x 803 x 1495 mm; (including Top Delivery Tray and User interface in max pos) 220 kg (Standard Configuration)

2 rolls, manual feed of cut sheet media

Automatic cutter included in the drawers for fast and easy roll media switching

A3, A2, A1, A0, B1, B2, B1_700, B2_700, B, C, D, E, B+, C+, D+, E+, E1, 880 mm, 860 mm, 800 mm, 700 mm, 660 mm, 620 mm, 460 mm, 500 mm, 440 mm, 430 mm, 310 mm, 297 mm

A3, A2, A1, A0, B1, B2, B1_700, B2_700, B, C, D, E, B+, C+, D+, E+, E1, 880 mm, 860 mm, 800 mm, 700 mm, 660 mm, 620 mm, 460 mm, 500 mm, 440 mm, 430 mm, 310 mm, 297 mm

60-110 g/m²

Length: Up to 200m, Width: 297-914 mm

76.2 mm (3 in) cores

420 mm

Plain Paper, Transparent, Translucent, Recycled Paper, Engineering Bond, Engineering Vellum, Colored Paper, Top Label Paper FSC, Red Label Paper PEFC, Black Label Paper PEFC, Green Label FSC, Polyester Film, Polyester Film Antistatic, Contrast Film, Clear Polyester Film, White Opaque Polyester Film, and Orika LPEX Rice Paper

Automatic width detection

- Automatic roll media selection for optimized productivity and media saving
- Automatic roll switching when end of roll is reached

High performance POWERsync+ controller with Windows 10 IoT Enterprise LTSC 2021, 64 bits

6 Core, 6 Thread, Core i5-8500 @4.10GHz 2x8 GB DDR4

Intel UHD Graphics 630, 1,1GHz

2x 500 GB, 7200 rpm (standard)

TPM 2.0

- Driver Select; Windows 8, Windows 8 64 bits, Windows 8.1, Windows 8.1 64 bits, Windows 10, Windows 10 64 bits, Windows Server 2012 64 bits, Windows Server 2012 R2 64 bits, Windows Server 2016 64 bits,
- Windows Server 2019 64 bits; Citrix XenApp 7.15, Citrix Virtual Apps 7 1811.1, Microfocus Enterprise Server OES 2018 • Driver Express; Windows 8, Windows 8 64 bits, Windows 8.1, Windows 8.1 64 bits, Windows 10, Windows 10 64 bits, Windows Server 2012 64 bits, Windows Server 2012 R2 64 bits, Windows Server 2016 64 bits, Windows Server 2019 64 bits; MacOS 10.13/10.14/10.15
- Publisher Select; Driver Select; Windows 8, Windows 8 64 bits, Windows 8.1, Windows 8.1 64 bits, Windows 10, Windows 10 64 bits
- Publisher Mobile; Android & iOS

2x Ethernet 100 Mbits/s, 1 Gbit/s, TCP/IP: DHCP, IPv4, IPv6, HTTPS Discovery: APIPA, WS-Discovery, SNMP WAVE interface

TIFF, JPEG, HPGL, HPGL2, DWF, C4, Calcomp 906/907/951, CALS, NIRS/NIFF

 LPR, FTP, WebDav • FTP • Pull from SMB, FTP • Pull from cloud (retrieve from ARC Collaborate, WebDAV based clouds) • HTTP/HTTPS (used by Publisher Express and PRISMAproduce Tech)
 Print from home folder (via access management license)

HTTP or HTTPS

Scanner size (WxDx H) and Weight 1097 x 308 x 140mm; 43 x 12 x 5.5in, 25 kg; 55 lbs ENVIRONMENTAL Sund Power Level Sound Power Level Standby and sleep; 24 dB, Print mode; 7.0 B(A) Sound Pressure Level O.42 mg/h <0.001 mg/m3 Heat Emission Ready; 71W; Active: 16 kW Power Requirements 100 - 240 V; 50/60Hz Power Requirements CE, TüV GS, cetecom advanced, c-UL-US, CB, CM, ENERGY STAR 30, FEMP, EPEAT, CCC, EAC, FCC Class A, VCCI Class A, RoHS Recyclables CE, TüV GS, cetecom advanced, c-UL-US, CB, CM, ENERGY STAR 30, FEMP, EPEAT, CCC, EAC, FCC Class A, VCCI Class A, RoHS Recyclables Printer: made of steel or highly recyclable platics: up to 95% of the engine can either be up cycled or recycled. Recyclables CLEARCONNECT WORKFLOW SOFTWARE Clear Connect print workflow software enables you to print in one go and efficiently create and submit print ipols safely from a variety of devices and sources. The ClearConnect Software Suite consists of a variety of applications with the same user interface. Creak, printer drivers that allow you to efficiently or the print from may application. Job Submission Protivers Chiver Select for Microsoft Windows); easy-to-use printer drivers that allow you to efficiently create and submit print plots are seven preview live with lestory, manage queue, manage and submit complex sets of documents from your desktop - to one, or two printers at time Publisher Konter Select for Microsoft Windows); easy-to-use printer drivers that allow you to efficiently and efficiently p				
Spin Chronhy Spin 201 x 20 m. Bit R 42 x 1 in (10.4 m 4 x 6m) Decembers & Rendelman Prepriorie consultation with a 000 Finds (1000) Decembers & Rendelman Standa distation (Nicker skip), Bitty, Rennerg, Hullmach, handmach, and hand, Bitts and Spin Standa, Bitts and Standa, Bitt				
Technology Resultion Progette expectation scape, 800 9 800 Pere (2014) Operation 2 Inspectation [Websel] (2016) inspectation [
decention 3 fixed subtract (Wess-up), Storp, Harmy, Abort, Jerson, March Landhart, Papers, Abort, Server, Serv	. ,			
Partaus: 2 Intel Protocols and a stream Security Security Features Security Features Device Security Features Security Features<				
UBB 20 Interface with indexing (bits, bardh, mitship, basker, all primages, about, foreing, Januar, Bordh, Korsen, Hangare, March, Hangare, Hangara, Hangare, Hanga		• • • • •		
Scality Features E-developing (PRE): If Therapy decays Control Lines (LTTRS, NVPD, 2, add Longer Decay, NVPD, Educed, NVPD, NVPD, 2000) Add 2000 Control Lines (LTTRS, NVPD, 2, add Longer Decay, NVPD, Educed, NVPD, 2000) Scality Features Scality Features Scality Features NVPD, 2000 Control Lines (LTTRS, NVPD, 2, add Longer Decay, NVPD, 2000) Access Management Scality Features Scality Features NVPD, 2000 Control Lines (LTTRS, NVPD, 2, add Longer Decay, LTDRS, NVPD, 2000) Access Management Scality Features Scality Features NVPD, 2000 Control Lines (LTTRS, NVPD, 2000) Courd Support Help provide acure access to device by uses leying in password on the Clear Courdian control Lines (LTTRS, NVPD, 2000) NVPD, 2000 Control Lines (LTTRS, NVPD, 2000) Courd Support Help provide acure access to device by uses leying in password on the Clear Courdian control Lines (LTTRS, 2000) NVPD, 2000 Control Lines (LTTRS, 2000) Scanners IDE provide acure acures to device by uses leying in password on the Clear Courdian control Lines (LTTRS, 2000) NVPD, 2000 Control Lines (LTTRS, 2000) Scanners IDE provide acure acures acures and provide control Lines (LTTRS, 2000) NVPD, 2000 Control Lines (LTTRS, 2000) Scanners IDE provide acure acures acutes acute	Features	USB 2.0 interface with indication light. Switch instantly between 2 languages, select from 19 languages; Czech, Danish, German, English, Spanish, Finnish, French, Hungarian, Italian, Japanese, Korean,		
BD21: A Life matchine, New Year Boy Construction (Enders), LDAP Integration, Action vanishing, LDAP Integration, Action vanis vanishing, LDAP Integration, Action vanishing, LDAP Integrati	SECURITY			
Access Management paired or gata access with a Dmart Card Dy connecting a clarit reader (incluing or outscletes). Authoritation is many by ungalache ungalache bung activity and weight Authoritation and metriculate claudic august is weight. Authoritation is many by and activity activity and the authoritation and metriculate claudic august is weight. All which the authoritation or metriculate activity and weight. All weights are and the specific Could Scanse Express IV Integrated Contact Image Series (CIS) Colour scanser with image Logic technology Scan Formas TEF, PDF, PDF, All A, PEG, CALS, multi-bage PDF, Multi-bage PDF, And multi-bage TIF Scan Formas Extension multitor of accessing the specific Could Scan Formas Extension multitor of accessing the specific Could Scan Formas Extension multitor of accessing the specific Could Scan Formas Extension multitor of accessing the specific Could Scan Formation Integrated Contact Image Series (CIS) Colour scanser with image Logic technology Scan Formation Integrated Contact Image Series (CIS) Colour scanser with image Logic technology Scan Formation Integrated Contact Image Series (CIS) Colour scanser with image Logic technology Scan Formation Integrated Contact Image Series (CIS) Colour scanser with image Logic technology Scan Formation Integrated Contact Image Series (CIS) Colour scanser with a many colon scolor scanser series (CIS) Colour scanser series (C	Security Features	802.1x Authentication, Network Protocol Enable/Disable, LDAP Integration, Active Directory Integration, User Authentication on Local ClearConnect User Panel and via Express WebTools (LDAP/Active Directory Credentials, Smart Card) for scan/copy/print. Configure HTTPS Certificates. Allow disabling TLS1.0 and 1.1 protocols (no response to network scan) and enable TLS 1.2 with stronger cipher. Embedded FIPS 140-2 Certified Trusted Platform Module (TPM) and BitLocker 256 AES Hard Disk encryption, Hard Disk Wipe, Configurable CA Certificate, Disable Network Ports and Protocols, Security Event Logging, Single Sign-on.		
Cloud Support e.g. Microsoft SharePort, Dropbox, Boxcom, boxnet, Gorgile DIVE, Microsoft OverDIVE and Microsoft OverDIVE	Access Management	panel or get access with a Smart Card by connecting a card reader (including contactless). Authorisation is		
Description Integrated Contact Image Sensor (CIS) Colours scanner with Image Logic technology Scan Resolution 600 x 600 dpi Scan Resolution 600 x 600 dpi Scan Remats TEF; PDF; ALPEG, CALLS, multi-page PDF, multi-page PDF, and multi-page ITFF Scan Protocol FTF, 9MB, scan to cloud (cuch to VebDAV based clouds) Scan Protocol Local USB Reik Arw, PTF, 9MB, scans to bood (cuch to VebDAV based clouds) Original Watch and Length 208mm - 966mm, 82n - 83n, automace with detectors, 208mm - 8200 mm, 82n - 830n, automace length detector, 100 mm, 033 in (con-rigid documents) Zacom (Copy) Li, Scale to media size, Scale to standard format, Custom 10 - 1000/S Original The/ness Builenin, Colourd original, Dark eriginal, Folded Imax/tect, Imax/text, transder, Linex/text, transd	Cloud Support	e.g. Microsoft SharePoint, Dropbox, Box.com, box.net, Google Drive, Microsoft OneDrive and Amazon Cloud Drive. The cloud user authentication can either be preconfigured by the administrator or		
Scan Resolution 600 x 600 dpl Scan Terrorists TITE, FDP, FDP, AJ, PEG, CALS, multi-page PDF, multi-page TDF Scan Terrorists Extensive multi-page TDF, SMB, scan to cloud (such to WebDAV based clouds) Scan Terrorists Local USB fitsh drive, FTP, SMB, smart Inbox on Controller, Optional Local Home Folder (LDAP), mobile device will vebDaV based clouds) Original Width and Length 203mm - 965mm; 82m - 38in, automatic width detection, 208mm - 16000mm; 82m - 630in, automatic length detection Original Width and Length 203mm - 965mm; 82m - 38in, automatic width detection, 208mm - 16000MK Scan (Copy) 11, Scale to media size, Scale to standard format, Cutom 10 - 1000% Original Tivickub (and Weight 100 / x 308 x 140mm; 43 x 12 x 55in, 25 kp; 55 lis ExV/IROMMENTAL Standby and skep; 42 R(A), Pinit mode; 70 R(A) Sound Pressure Level Standby and skep; 42 R(A), Pinit mode; 50 dB Sound Pressure Level Standby and skep; 42 R(A), Pinit mode; 50 dB Original Tivike, made Environmental Labels CE, TW 6, Keator 164, Web, Ready mode; 64 W, Active mode; 154 TW Standby and skep; 42 R(A), Pinit mode; 50 dB CE, TW 6, Ceator advice of standard format, Cutom of a scale of standard format, Cutom of scale of standard format, Cutom of scale of standard format, Cutom of scale of	SCANNER EXPRESS IV			
Scan Resolution 600 x 600 dpl Scan Terrorists TITE, FDP, FDP, AJ, PEG, CALS, multi-page PDF, multi-page TDF Scan Terrorists Extensive multi-page TDF, SMB, scan to cloud (such to WebDAV based clouds) Scan Terrorists Local USB fitsh drive, FTP, SMB, smart Inbox on Controller, Optional Local Home Folder (LDAP), mobile device will vebDaV based clouds) Original Width and Length 203mm - 965mm; 82m - 38in, automatic width detection, 208mm - 16000mm; 82m - 630in, automatic length detection Original Width and Length 203mm - 965mm; 82m - 38in, automatic width detection, 208mm - 16000MK Scan (Copy) 11, Scale to media size, Scale to standard format, Cutom 10 - 1000% Original Tivickub (and Weight 100 / x 308 x 140mm; 43 x 12 x 55in, 25 kp; 55 lis ExV/IROMMENTAL Standby and skep; 42 R(A), Pinit mode; 70 R(A) Sound Pressure Level Standby and skep; 42 R(A), Pinit mode; 50 dB Sound Pressure Level Standby and skep; 42 R(A), Pinit mode; 50 dB Original Tivike, made Environmental Labels CE, TW 6, Keator 164, Web, Ready mode; 64 W, Active mode; 154 TW Standby and skep; 42 R(A), Pinit mode; 50 dB CE, TW 6, Ceator advice of standard format, Cutom of a scale of standard format, Cutom of scale of standard format, Cutom of scale of standard format, Cutom of scale of	Description	Integrated Contact Image Sensor (CIS) Colour scanner with Image Logic technology		
Scan Templates Extensive number of scan templates to standardise common scan settings and destinations Scan Protocol FIF, SMB, scan to cloud (push to WebDAV based clouds) Scan Destination Incoll Set Bardines FTF, SMB, Scan to Coord (push to WebDAV Clouds) Original Width and Length 200mm - 965mm 8.din - 865m, 845m, 845m, 945m, 1000 mm 8.2in + 630n, automatic length detection Bffercive Scan Maximum 0.8 mm; 0.03 in (non-rigid documents) Original Thickness Maximum 0.8 mm; 0.03 in (non-rigid documents) Zoom (Copy) 11, Scale to media size, Scale to standard format, Custom 10 - 1000% Original Thickness Busenth: Coloured original, Draket Inney/Lexit. Lines/Lexit standard, Lines/Lexit and Lines/Lines/Lines/Lines/Lines/Lines/Lines/Lines/Lines/Lines/Lines/Lines/Lines/Line				
Scan Protocol FTP. SMB, scan to cloud (puth to WebDAV based clouds) Scan Destination Local USB fish drive, FTP, SMB, smart holox on Controller, Optimal Local Home folder (LDAP), mobile diverse via WebTod6 Meblio, WebDAV Clouds Original Width and Length 208mm - 965mm; 82in - 38in, automatic width detection, 208mm - 1600mm; 82in - 630in, automatic length detection Effective Scan Width 932 mm Original Trickness Maximum 0.8 mm; 0.03 in (non-rigid documents) Zoom (Copy) 11, Scale to media size, Scale to standard format, Custom: 10 - 1000% Original Trickness Blueprint, Coloured original, Dark original, Fröded linex/text, Linex/text standard, Linex/text draft, Photo, Map, Artwork Scanner size (WADx H) and Weight 1097 x 308 x 140mm; 43 x 12 x 55m, 25 kg, 55 lbs EVNIROMEENTAL Environmental Long Sound Pressure Level Standby and sleep; 24 B(A). Print mode: 58 dB Ozore Concurtation 042 mg/h <0001 mg/m3	Scan Formats	TIFF, PDF, PDF/A, JPEG, CALS, multi-page PDF, multi-page PDF/A and multi-page TIFF		
Scan Destination Local USB flash drive, FTP, SMB, Smart I libox on Controller, Optional Local Home folder (LDAP), mobile device via VeBF106k Mobile, VeBDAV Clouds Original Width and Longth 208mm - 660mm, 82m - 30in, automatic width detection, 208mm - 16000mm, 82m - 630in, automatic length detection Griginal Thickness Original Thickness Maximum 0.8 mm; 0.03 in (non-rigid documents) 200m (Copy) 11, Scale to media size, Scale to standard formst, Custom: 10 - 1000% Original Thickness Biuprint, Colourd original, Dark original, Folded lines/fext, Lines/text standard, Lines/text and: Photo, Map, Artwork Scanne Size (WDA): H) and Weight 1997 x 308 x 140mm, 45 x 12 x 55in, 25 kg; 55 lbs ENVIRONMENTAL Standby and sleep; 24 dB, Print mode; 7.0 B(A) Sound Power Level Standby and sleep; 24 dB, Print mode; 7.0 B(A) Sound Power Requirements 100 - 240 v; 50/60Hz Power Requirements 100 - 240 v; 50/60Hz Power Requirements 200 stand v; 30/60Hz Power Requirements 26 kg monde; c2W, Ready mode; 64 W, Active mode; 1547 W Starty/EMC marks & Environmental Labels CE: TW GS, createon admixed cuLLA; CE: RCMC NERKOY STAR 30, FIPE AT, CCC; EAC, FCC Cless A, VCD Cless A, Reids Alexa Construct Printer: mode of stael or highly recyclabel plastics; up to 95% of the engine can other bug to cycle of recycled Prennaing 35 km e not t	Scan Templates	Extensive number of scan templates to standardise common scan settings and destinations		
Start Desired upon mobile device via WebTrods Mobile, WebDAV Clouds Original Width and Length 200mm - 965mm; 8.2in - 38in, automatic width detection, 200mm - 16000m; 8.2in - 630in, automatic length detection Ofriginal Thickness Maximum 0.8 mm; 0.03 in (non-rigid documents) I. Scale to media size, Scale to standard format, Custom: 0.1000% 0.000% Original Thickness Blueprint, Coloured original, Dark original, Folded lines/text standard, Lines/text	Scan Protocol	FTP, SMB, scan to cloud (push to WebDAV based clouds)		
Effective Scan Width 932 mm Original Thickness Maximum 0.8 mm; 0.05 in (non-rigid documents) Zoom (Copy) 13, Scale to media size, Scale to standard format, Custom: 10-1000% Original Type Presets Blueprint. Coloured original Dark original, Folded lines/text, Lines/text standard, Lines/text draft, Photo, Map, Artwork Scanner size (WidX H) and Weight 1097 x 308 x 140mm; 43 x 12 x 5.5n, 25 kg; 55 lbs ENVIRONMENTAL Standby and sleep; 42 B(A), Print mode: 7.0 B(A) Sound Power Level Standby and sleep; 24 dB, Print mode: 58 dB Ozone Concentration 0.42 mg/h <0.001 mg/m3	Scan Destination			
Original Thickness Maximum 0.8 mm; 0.03 in (non-rigid documents) Zoom (Copy) 11, Scale to media size, Scale to standard format, Custom: 10 - 1000% Original Type Presets Blueprint, Coluced original, Dark original, Folded Iney/toxt, Lines/text standard, Lines/text draft, Photo, Map, Artwork Scanner size (WKOK H) and Weight 1097 x 308 x 120 x 5.5in, 25 kg; 55 lbs ENVIRONMENTAL Standby and sleep: 42 B(A), Print mode: 7.0 B(A) Sound Power Level Standby and sleep: 24 dB, Print mode: 58 dB Ozone Concentration 0.42 mg/h <0.001 mg/m3	Original Width and Length	208mm - 965mm; 8.2in - 38in, automatic width detection, 208mm - 16000mm; 8.2in - 630in, automatic length detection		
Zoom (Copy) 11, Scale to media size, Scale to standard format, Custom: 10 - 1000% Original Type Presets Blueprint, Coloured original, Dark original, Folded lines/text, Lines/text draft, Photo, Map, Artwork Scanner size (WXDx H) and Weight 1097 x 308 x 140mm; 43 x 12 x 5.5in, 25 kg; 55 lbs ENVIRONMENTAL Standby and sleep: 42 B(A), Print mode: 70 B(A) Sound Power Level Standby and sleep: 42 B(A), Print mode: 70 B(A) Sound Power Level Standby and sleep: 42 dB, Print mode: 58 dB Ozone Concentration 0.42 mg/h <0.001 mg/m3	Effective Scan Width	932 mm		
Original Type Presets Blueprint. Coloured original. Dark original, Folded lines/text. Lines/text standard. Lines/text draft, Photo, Map, Artwork Scanner size (WXDx H) and Weight 1097 x 308 x 140mm; 43 x 12 x 5.5 in, 25 kg; 55 lbs ENVIRONMENTAL Sound Power Level Sound Power Level Standby and sleep: 4.2 B (A), Print mode: 7.0 B(A) Sound Power Level Standby and sleep: 2.4 dB, Print mode: 58 dB Ozone Concentration 0.42 mg/h <0.001 mg/m3	Original Thickness	Maximum 0.8 mm; 0.03 in (non-rigid documents)		
Scanner size (WxDx H) and Weight 1097 x 308 x 140mm; 43 x 12 x 5.5in; 25 kg; 55 lbs ENVIRONMENTAL Standby and sleep: 42 B(A), Print mode: 7.0 B(A) Sound Pressure Level Standby and sleep: 24 dB, Print mode: 58 dB Ozone Concentration 0.42 mg/h < 0.001 mg/m3	Zoom (Copy)	1:1, Scale to media size, Scale to standard format, Custom: 10 - 1000%		
ENVIRONMENTAL Sound Power Level Standby and sleep: 4.2 B(A), Print mode: 7.0 B(A) Sound Pressure Level Standby and sleep: 24 dB, Print mode: 7.0 B(A) Conce Concentration 0.42 mg/h × 0.001 mg/m3 Heat Emission Ready: 7UK; Active: 16 kW Power Requirements 100 - 240 V; 50/60Hz Power Consumption Sleep mode: <2 W, Ready mode: 64 W, Active mode: 1547 W	Original Type Presets	Blueprint, Coloured original, Dark original, Folded lines/text, Lines/text standard, Lines/text draft, Photo, Map, Artwork		
Sound Power Level Standby and sleep: 42 B(A), Print mode: 7.0 B(A) Sound Pressure Level Standby and sleep: 24 dB, Print mode: 58 dB Ozone Concentration 0.42 mg/h <0.001 mg/m3	Scanner size (WxDx H) and Weight	1097 x 308 x 140mm; 43 x 12 x 5.5in, 25 kg; 55 lbs		
Sound Pressure Level Standby and sleep: 24 dB, Print mode: 58 dB Ozone Concentration 0.42 mg/h <0.001 mg/m3				
Ozone Concentration 0.42 mg/h < 0.001 mg/m3	Sound Power Level	Standby and sleep: 4.2 B(A), Print mode: 7.0 B(A)		
Heat Emission Ready: 71W; Active: 16 kW Power Requirements 100 - 240 V; 50/60Hz Power Consumption Sleep mode: <2 W, Ready mode: 64 W, Active mode: 1547 W	Sound Pressure Level	Standby and sleep: 24 dB, Print mode: 58 dB		
Power Requirements 100 - 240 V; 50/60Hz Power Consumption Sleep mode: <2 W, Ready mode: 64 W, Active mode: 1547 W	Ozone Concentration	0.42 mg/h <0.001 mg/m3		
Power Consumption Sleep mode: <2 W, Ready mode: 64 W, Active mode: 1547 W Safety/EMC marks & Environmental Labels CE, TüV GS, cetecom advanced, c-UL-US, CB, RCM, ENERGY STAR 3.0, FEMP, EPEAT, CCC, EAC, FCC Class A VCIC Class A RoHS Recyclables Printer: made of steel or highly recyclable plastics: up 0 95% of the engine can either be up cycled or recycled. Remaining 5% are non toxic waste. Prints: Deinkability certificate, Toner: Toner bottles made from on average 50% recycled HDPE (High Density Polyethylene) CLEARCONNECT WORKFLOW SOFTWARE ClearConnect print workflow software enables you to print in one go and efficiently create and submit print jobs safely from a variety of devices and sources. The ClearConnect Software Suite consists of a variety of applications with the same user interface. Create, retrieve and/or send jobs from:	Heat Emission	Ready: 71W; Active: 1.6 kW		
Safety/EMC marks & Environmental Labels CE, TUV GS, cetecom advanced, -UL-US, CB, RCM, ENERGY STAR 3.0, FEMP, EPEAT, CCC, EAC, FCC Class A VCCI Class A RoHS Recyclables Printer: made of steel or highly recyclable plastics: up to 95% of the engine can either be up cycled or recycled. Remaining 5% are non toxic waste. Prints: Deinkability certificate, Toner: Toner bottles made from on average 50% recycled HDPE (High Density Polyethylene) CLEARCONNECT WORKFLOW SOFTWARE ClearConnect print workflow software enables you to print in one go and efficiently create and submit print lobs safely from a variety of devices and sources. The ClearConnect Software Suite consists of a variety of applications with the same user interface. Create, retrieve and/or send jobs from: Job Submission • The Drivers (Driver Select for Microsoft Windows); easy-to-use printer drivers that allow you to effectively an one or two print into may application. • Publisher Submits or print ibbs via your mobile phone app supporting IOS and Android • Publisher Supers - Easily submit your print jobs via bevice or external locations. Zoom and pan to different areas - even preview live while scanning or copying to avoid errors. Smart Inbox Personalized Smart Inbox with history, manage queue, manage history. WebTools Express, secured controller access Mobile and Cloud Print from and scan to the cloud application of your choice. With the help of mobile applications such as Publisher Mobile, the printer can be easily accessed and used from any location Draine demangement WebTools Express provides admininistrators the tools to manage the device remotely via	Power Requirements	100 - 240 V; 50/60Hz		
Recyclables Printer: made of steel or highly recyclable plastics: up to 95% of the engine can either be up cycled or recycled. Remaining 5% are non toxic waste. Prints: Deinkability certificate, Toner: Toner bottles made from on average 50% recycled HDPE (High Density Polyethylene) CLEARCONNECT WORKFLOW SOFTWARE ClearConnect print workflow software enables you to print in one go and efficiently create and submit print jobs safely from a variety of devices and sources. The ClearConnect Software Suite consists of a variety of applications with the same user interface. Create, retrieve and/or send jobs from: Job Submission • The Drivers (Driver Select for Microsoft Windows); easy-to-use printer drivers that allow you to effectively and efficiently print from any application. • Publisher Select - Easily create, manage and submit complex sets of documents from your desktop - to one, or two printers at time • Publisher Select - Easily create, manage and submit complex sets of documents from your desktop - to one, or two printers at time • Publisher Select Submit print jobs via your mobile phone app supporting iOS and Android • Publisher Select Submit print jobs via the web independent of your web browser • ClearConnect User Panel - Print, Copy or Scan is as easy as using a table with the multi-to-du user panel. Pull up a document from your Smart Inbox, USB device or external locations. Zoom and pan to different areas - even preview live while scanning or copying to avoid errors. Gueue Management Spool memory provides a queuing system for print and copy jobs. This enables multiple users to send print and copy jobs at the same time. Mobile and Cloud Print from and scan to the cloud application of your choice. With the help of mobile applications such as Publisher Mobile, the printe	Power Consumption	Sleep mode: <2 W, Ready mode: 64 W, Active mode: 1547 W		
Recyclables Remaining 5% are non toxic waste. Prints: Deinkability certificate, Toner: Toner bottles made from on average 50% recycled HDPE (High Density Polyethylene) CLEARCONNECT WORKFLOW SOFTWARE ClearConnect print workflow software enables you to print in one go and efficiently create and submit print jobs safely from a variety of devices and sources. The ClearConnect Software Suite consists of a variety of applications with the same user interface. Create, retrieve and/or send jobs from: Job Submission • The Drivers (Driver Select for Microsoft Windows); easy-to-use printer drivers that allow you to effectively and efficiently print from any application. • Publisher Select + Easily create, manage and submit complex sets of documents from your desktop - to one, or two printers at a time • Publisher Select Software sets of documents from your desktop - to one, or two printers at a time • Smart Inbox Personalized Smart Inbox with history, manage queue, manage history, WebTools Express, secured controller access Queue Management Spool memory provides a queuing system for print and copy jobs. This enables multiple users to send print and copy jobs. This enables multiple users to send print and copy jobs. This enables multiple users to send print and copy jobs. This enables multiple users to send printer manage the device remotely via the web: e.g., check printer satus, define default settings for print, copy and scan, define access, security, accounting,	Safety/EMC marks & Environmental Labels	CE, TüV GS, cetecom advanced, c-UL-US, CB, RCM, ENERGY STAR 3.0, FEMP, EPEAT, CCC, EAC, FCC Class A, VCCI Class A, RoHS		
ClearConnect print workflow software enables you to print in one go and efficiently create and submit print jobs safely from a variety of devices and sources. The ClearConnect Software Suite consists of a variety of applications with the same user interface. Create, retrieve and/or send jobs from: Job Submission • The Drivers (Driver Select for Microsoft Windows); easy-to-use printer drivers that allow you to effectively and efficiently print from any application. • Publisher Select - Easily create, manage and submit complex sets of documents from your desktop - to one, or two printers at a time • Publisher Mobile - Submit print jobs via your mobile phone app supporting iOS and Android • Publisher Mobile - Submit print jobs via the web independent of your web browser • ClearConnect User Panel - Print, Copy or Scan is as easy as using a tablet with the multi-touch user panel. Pull up a document from your Smart Inbox, USB device or external locations. Zoom and pan to different areas - even preview live while scanning or copying to avoid errors. Smart Inbox Personalized Smart Inbox with history, manage queue, manage history, WebTools Express, secured controller access Queue Management Spool memory provides a queuing system for print and copy jobs. This enables multiple users to send print and copy jobs at the same time. Mobile and Cloud Print from and scan to the cloud application of your choice. With the help of mobile applications such as Publisher Mobile, the printer can be easily accessed and used from any location	Recyclables	Remaining 5% are non toxic waste. Prints: Deinkability certificate,		
ClearConnect print workflow software enables you to print in one go and efficiently create and submit print jobs safely from a variety of devices and sources. The ClearConnect Software Suite consists of a variety of applications with the same user interface. Create, retrieve and/or send jobs from: Job Submission • The Drivers (Driver Select for Microsoft Windows); easy-to-use printer drivers that allow you to effectively and efficiently print from any application. • Publisher Select - Easily create, manage and submit complex sets of documents from your desktop - to one, or two printers at a time • Publisher Mobile - Submit print jobs via your mobile phone app supporting iOS and Android • Publisher Mobile - Submit print jobs via the web independent of your web browser • ClearConnect User Panel - Print, Copy or Scan is as easy as using a tablet with the multi-touch user panel. Pull up a document from your Smart Inbox, USB device or external locations. Zoom and pan to different areas - even preview live while scanning or copying to avoid errors. Smart Inbox Personalized Smart Inbox with history, manage queue, manage history, WebTools Express, secured controller access Queue Management Spool memory provides a queuing system for print and copy jobs. This enables multiple users to send print and copy jobs at the same time. Mobile and Cloud Print from and scan to the cloud application of your choice. With the help of mobile applications such as Publisher Mobile, the printer can be easily accessed and used from any location	CLEARCONNECT WORKFLOW SOFTWARE			
Job Submissionand efficiently print from any application. • Publisher Select - Easily create, manage and submit complex sets of documents from your desktop - to one, or two printers at a time • Publisher Mobile - Submit print jobs via your mobile phone app supporting iOS and Android • Publisher Mobile - Submit print jobs via your mobile phone app supporting iOS and Android • Publisher Express - Easily submit your print jobs via the web independent of your web browser • ClearConnect User Panel - Print, Copy or Scan is as easy as using a tablet with the multi-touch user panel. Pull up a document from your Smart Inbox, USB device or external locations. Zoom and pan to different areas - even preview live while scanning or copying to avoid errors.Smart InboxPersonalized Smart Inbox with history, manage queue, manage history, WebTools Express, secured controller accessQueue ManagementSpool memory provides a queuing system for print and copy jobs. This enables multiple users to send print and copy jobs at the same time.Mobile and CloudPrint from and scan to the cloud application of your choice. With the help of mobile applications such as Publisher Mobile, the printer can be easily accessed and used from any locationDevice ManagementWebTools Express provides administrators the tools to manage the device remotely via the web: e.g. check printer status, define default settings for print, copy and scan, define access, security, accounting,		jobs safely from a variety of devices and sources. The ClearConnect Software Suite consists of a variety of		
Queue Management Spool memory provides a queuing system for print and copy jobs. This enables multiple users to send print and copy jobs at the same time. Mobile and Cloud Print from and scan to the cloud application of your choice. With the help of mobile applications such as Publisher Mobile, the printer can be easily accessed and used from any location Device Management WebTools Express provides administrators the tools to manage the device remotely via the web: e.g. check printer status, define default settings for print, copy and scan, define access, security, accounting,	Job Submission	 and efficiently print from any application. Publisher Select - Easily create, manage and submit complex sets of documents from your desktop - to one, or two printers at a time Publisher Mobile - Submit print jobs via your mobile phone app supporting iOS and Android Publisher Express - Easily submit your print jobs via the web independent of your web browser ClearConnect User Panel - Print, Copy or Scan is as easy as using a tablet with the multi-touch user panel. Pull up a document from your Smart Inbox, USB device or external locations. Zoom and pan to different 		
Queue Management copy jobs at the same time. Mobile and Cloud Print from and scan to the cloud application of your choice. With the help of mobile applications such as Publisher Mobile, the printer can be easily accessed and used from any location Device Management WebTools Express provides administrators the tools to manage the device remotely via the web: e.g. check printer status, define default settings for print, copy and scan, define access, security, accounting,	Smart Inbox	Personalized Smart Inbox with history, manage queue, manage history, WebTools Express, secured controller access		
Mobile and Cloud Publisher Mobile, the printer can be easily accessed and used from any location WebTools Express provides administrators the tools to manage the device remotely via the web: e.g. check printer status, define default settings for print, copy and scan, define access, security, accounting,	Queue Management	Spool memory provides a queuing system for print and copy jobs. This enables multiple users to send print and copy jobs at the same time.		
Device Management e.g. check printer status, define default settings for print, copy and scan, define access, security, accounting,	Mobile and Cloud			
remote shutdown, software update and restart, power on/off timer, system behavior, queue management, license management, view, create, edit and delete stamp templates, etc.	Device Management	e.g. check printer status, define default settings for print, copy and scan, define access, security, accounting, remote shutdown, software update and restart, power on/off timer, system behavior, queue management,		



Part Code : 9600W344

CANON INDIA PVT. LTD. 7th Floor, Tower B, Building No. 5, DLF Epitome DLF Phase III, Gurugram - 122002

Bengaluru

Canon India Pvt. Ltd. 6th floor, Embassy One Pinnacle Tower No. 8 Ist C Main, Bellary Road, Ganganagar, Bengaluru - 560032

Kolkata

Canon India Pvt. Ltd PS Arcadia Central, 6th floor, 4A, Abanindra Nath Thakur Sarani (Camac Street) Kolkata - 700017

Mumbai

Canon India Pvt. Ltd. 19th Floor, Commerz II, Wing A, International Business Park, Oberoi Garden City, Off Western Express Highway, Goregaon (East), Mumbai - 400063

Hyderabad

Canon India Pvt. Ltd. The Belvedere H.No.: 6-3-891/892, 2nd Floor, Raj Bhawan Road, Somajiguda, Hyderabad - 500082 Tel: 040-39995800 Fax: 040-39995801

Chennai


Canon India Pvt. Ltd. "SKCL" Infinite Towers, 8th Floor, Plot No.: A21 & A22, Thiru-Vi-Ka Industrial Estate, Guindy, Chennai - 600032 Tel:-044-49080000 Fax: 044-49080001

| Tel: 0124-4160000 | Call: 1800 208 3366 | 1860 180 3366

Canon India Pvt. Ltd. Office No.: 404 & 405, Senapati Bapat Road

Pune

Senapati Bapat Road (Bhamburda), Shivaji Nagar, Pune - 411 016 Tel: 020-6680 9600 Fax: 020-66809602



👉 🛛 Please return end-of-life product for environmentally safe disposal. For details, visit https://in.can

Illustrations and specifications do not necessarily apply to products and services offered in each local market. Technical specifications are subject to change without prior notice.

This document is for information purpose only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.

Warning: Unauthorized recording of copyrighted materials may infringe the rights of copyright owners and be contrary to copyright laws.