# imageCLASS LBP811Cx





# Outstanding A3 Colour Laser Printer for the Dynamic Business

Enhance productivity in any business environment with the imageCLASS LBP811Cx. This versatile printer supports a variety of media sizes, allowing businesses to efficiently manage a wide range of printing tasks. An ideal choice to boost workplace productivity.



HIGH-YIELD CARTRIDGES



### EXPANDABLE PAPER CAPACITY

Designed to meet your growing business needs, the printer is suitable for handling large volume print jobs with an expandable paper capacity of up to 2 550 sheets and can support a diverse range of print media sizes from A5 to A3.



Automatic duplex printing allows for sustainable twosided printing, which helps to reduce paper usage and lower carbon footprints.



# SECURE & SEAMLESS CONNECTIVITY

With Dual Network, you can share the printer across two different networks simultaneously. This enables administrators to perform network segmentation without compromising on security.



# ENHANCED DATA PROTECTION

TLS 1.3 encrypts and protects data from sniffing, spoofing and tampering, as well as allowing the system's integrity to be monitored during startup.



#### SPECIFICATIONS / imageCLASS LBP811Cx

381	CIFICATIONS / I	magec	LASS LEPOIN					
	Printing Method		Colour Laser Beam Printing			Wired	USB 2.0, 10Base-T/100Base-TX/1000Base-T	
		A4*1 (mono/colour)		30 / 30 prints/min		Standard Interfaces	Wireless	IEEE 802.11b/g/n (Infrastructure Mode, Access Point Mode)
	Print Speed	Letter*1 (mono/colour)		30 / 30 prints/min				
		2-Sided, A4 (mono/colour)		28.9 / 28.9 images/min		Network Protocol	Print	TCP/IP (LPD/RAW/IPP/IPPS/FTP/WSD)
		A3 (mono/colour)		15 / 15 images/min				
	Print Resolution			600 x 600 dpi 1 200 x 1 200 dpi	TWARE	Network Security	Wired	IP/Mac Address Filtering, HTTPS, SNMPv3, IEEE 802.1X, IPsec, TLS 1.3, Dual Network Support
	Print Quality with Image Refinement Technology			1 200 x 1 200 dpi (equivalent)	& SOF		Wireless	Infrastructure Mode: WEP (64/128 bit), WPA-PSK (TKIP/AES), WPA2-PSK (TKIP/AES), WPA3-SAE (AES), WPA-EAP (AES), WPA2-EAP (AES), WPA3-EAP (AES), IEEE 802.1X, Access Point Mode: WPA2-PSK (AES)
PRINT	Warm-Up Time (From Power On)			22 s or less	1TY 8			
•	First Print Out Time <sup>*2</sup> (approx.) A4 (mono/colour)			11.3 / 12.6 s	VECTIV			
	Recovery Time (From Sleep Mode)			7 s or less	SONI			Canon PRINT, Canon Print Service (Android),
	Print Language			UFR II, PCL 6, Adobe® PostScript® 3™	Ŭ	Mobile/Cloud Printing Solutions		AirPrint <sup>®</sup> , Mopria <sup>®</sup> Print Service, Microsoft Universal Print
	Auto Duplex Print			Yes				Windows 10/11, Windows Server 2016/2019/2022,
	Print Margins Supported File Format for USB Direct Print			Top/Bottom/Left/Right margin: 5 mm Top/Bottom/Left/Right margin: 10 mm (Envelope) JPEG, PDF, TIFF, XPS		Operating System Cor	npatibility*4	macOS 10.14 or later, Linux, ChromeOS
						Other Features		Force Hold Print, Department ID, Secure Print
						Available Software		Printer Driver, Toner Status
	Input Tray Capacity (Plain Paper, 80 g/m²)	Standard	Cassette	250 sheets		Device Memory		2 GB
			Multi-Purpose	100 sheets		Display		5-Line LCD
			Tray			Power Requirements		AC 220 - 240 V, 50/60 Hz
		Optional	Paper Feeder	550 sheets 2 550 sheets			Operation	570 W (max. 1 710 W)
	Maximum		(Standard + 4 Paper Feeders) 250 sheets	-	Power Consumption*5 (approx.)	Standby	30 W	
	Output Tray Capacity (Plain Paper, 80 g/m²)					Sleep	1 W	
		Cassette/Paper Feeder*3 (optional)		A3, A4, A5, A6, B4, B5, B6, Ledger, Letter, Executive, Statement, Foolscap, Government Letter, Government Legal, Indian Legal, Custom (min. 85 x 148 mm to max. 297 x 431.8 mm)	< <	Operating Environment	Temperature	10 - 30°C
							Humidity	20 - 80% RH (no condensation)
						Monthly Duty Cycle <sup>*6</sup>		100,000 pages
					Ŭ	Dimensions (W x D x H) (approx.)		499 x 525 x 340 mm
DLING		Multi-Purpose Tray		A3, A4, A5, A6, B4, B5, B6, Ledger, Legal, Letter, Executive, Statement, Foolscap, Government Letter, Government Legal, Indian Legal, Index Card, Postcard, Envelope (COM10, Monarch, DL, C5), Custom (min. 64 x 120 mm) to max. 297 x 1.320 mm)		Weight <sup>*7</sup> (approx.)		32.5 kg
PAPER HANDLING	Media Size					Toner Cartridge <sup>*e</sup>	Standard	Cartridge 076 Black: 15 000 prints (Bundled: 5 000 prints)
PAPE								Cartridge 076 Cyan, Magenta, Yellow: 14 000 prints (Bundled: 3 000 prints)
		2-Sided Printing		A3, A4, A5, B4, B5, Ledger, Legal, Letter, Executive, Foolscap, Government Letter, Government Legal,			Low	Cartridge 076L Black: 7 000 prints Cartridge 076L Cyan, Magenta, Yellow: 5 000 prints
				Custom (min. 148 x 148 mm to max. 297 x 431.8 mm)		Paper Feeder		Paper Feeder PF-L1 (550 sheets)
	Media Type			Plain Paper, Recycled Paper, Label, Postcard, Envelope	OPTIONAL ACCESSORIES	Plain Pedestal		Plain Pedestal BA1
	Cassette/Paper Feeder		60 - 163 g/m²	NAL				
		Multi-Purpose Tray		60 - 250 g/m²	0E	Barcode Printing Kit		Barcode Printina Kit-D1E
	Media Weight	Multi-Purp	ose Iray	00 200 g/m	ö	Barcode Printing Kit		Barcode Printing Kit-D1E

\*1 Print speed is measured based on internal testing using A4/Letter size paper printed with 100% print ratio to original on one-sided paper. Internal testing involved continuously printing the same one page of content on plain paper. Print speed may vary depending on paper type, paper size or paper feeding direction.

\*<sup>2</sup> First print out time is measured based on internal test procedure and may vary. When the printer is in the ready state, this is the time from receiving the print instruction from the controller to printing one sheet and finishing paper ejection.

<sup>\*3</sup> Custom size for paper feeder: min. 85 x 148 mm to max. 297 x 431.8 mm; additional attachment may be required.

\*4 The latest drivers for Windows, Windows Server, macOS and Linux can be downloaded from https://asia.canon/support website when available.

\*5 Power consumption is based on internal test procedure and may vary.

\*6 Monthly Duty Cycle value provides a means of comparison for product robustness in relation to other Canon laser printer devices, and does not refer to actual maximum image output per month.

\*7 Excluding toner cartridge.

\*8 Toner cartridge is in accordance with ISO/IEC 19798.



#### CANON INDIA PVT. LTD.

7th Floor, Tower B, Building #5, DLF Epitome Building, DLF Phase III, Gurugram-122002 Ph.: 0124-4160000 | Fax: 0124-4160011 | Web: in.canon

DEALER'S STAMP

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weight and dimensions are approximates. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.