





## PROFESSIONAL EFFICIENCY



#### **EASE AT EVERY TOUCH**

The imageCLASS series' vari-angle 127mm (5-inch) touchscreen LCD display allows greater viewing flexibility with a touch, and makes navigation simple, convenient and intuitive.



#### **HIGH PRINT YIELDS**

With print yields of up to 7 600 pages (Black) and 5 900 pages (Colour), experience less frequent toner replacements with the optional high capacity toner cartridges.



#### **WIRELESS AND MOBILE CONNECTIVITY**

Print on the go using your mobile device for fast data transfers, through a selection of apps such as Canon PRINT Business, Apple® AirPrint®, Google Cloud Print™, Mopria® and Canon Print Service.



#### **SIMPLIFY WORKFLOWS**

With the built in Application Library, use applications to ease your work process. The Fax and Store application allows you to keep a backup of sent faxes for easy reference.



#### **PREVIEW AND PRINT**

Preview your documents before printing with Memory Media. (Supports TIFF, JPEG and PDF files)

# TRUE VIVID COLOUR



#### PRINTOUTS ALMOST TRUE TO LIFE

With  $V^2$  Colour Technology, expect commanding prints that leave a great impression during business presentations. Anticipate incredible and striking visuals with an expanded colour palette on every print.

# **EFFORTLESS MAINTENANCE**



### **ALL-IN-ONE, EASY UPKEEP**

With the combination of a photosensitive drum, cleaning unit and toner reservoir, Canon's All-in-One toner cartridge gets printing tasks done effortlessly, with minimal maintenance. The auto toner seal removal system also adds convenience when replacing the cartridge.

## **ECO-SAVINGS**

## **AUTO DUPLEX PRINTING**

Cut down costs and save on paper by printing most of your office documents with the double-sided printing function.

SPECIFICATIONS		MF645Cx	MF746Cx	
		WIF645CX	WIF/40CX	
PRINT				
Printing Method				
Print Speed	A4	Up to 21 / 21 pages/min (Mono/Colour)	Up to 27 / 27 pages/min (Mono/Colour)	
	Letter	Up to 22 / 22 pages/min (Mono/Colour)	Up to 28 / 28 pages/min (Mono/Colour)	
	2-Sided	Up to 12 / 12 pages/min (Mono/Colour)	Up to 21 / 21 pages/min (Mono/Colour)	
Print Resolution		600 x 600 dpi		
Print Quality with Image Refinement Technology		1 200 x 1 200 dpi (equivalent)		
Warm up Time (From Power On)		13.0 s or less		
First Printout Time (FPOT)	A4	Approx. 10.4 / 10.5 s (Mono/Colour)	Approx 7.7 / 8.6 s (Mono/Colour)	
	Letter	Approx. 10.3 / 10.3 s (Mono/Colour)	Approx. 7.5 / 8.5 s (Mono/Colour)	
Recovery Time (From Sleep Mode)		Approx. 6.1 s or less		
Print Language		UFR II, PCL 6, Adobe® PostScript® 3™		
Auto Duplex Print		Standard		
Available Paper Size for Auto Duplex Print		A4, B5, Letter, Legal, Executive, Foolscap, Indian Legal		
Supported File Format for USB Direct Print		Supported File Format: JPEG, TIFF, PDF		
Print Margins		5 mm - top, bottom, left and right (Envelope: 10 mm)		
Print Features		Paster, Booklet, Watermark, Page Composer, Toner Saver		
СОРУ				
Copy Speed	A4	Up to 21 / 21 pages/min (Mono/Colour)	Up to 27 / 27 pages/min (Mono/Colour)	
	Letter	Up to 22 / 22 pages/min (Mono/Colour)	Up to 28 / 28 pages/min (Mono/Colour)	
Copy Resolution		600 x 60	'	
First Copy Time (FCOT)	A4	Approx. 11.4 / 13.4 s (Mono/Colour)	Approx. 9.8 / 11.3 s (Mono/Colour)	
riisi copy liille (rcor)	Letter	Approx. 11.2 / 13.1 s (Mono/Colour)	Approx. 9.5 / 11.1 s (Mono/Colour)	
Maximum Number of Copies		Up to 999	copies	
Reduce/Enlargement		25 - 400% in 1%	Sincrements	
Copy Features		Frame Erase, Collate, 2 on 1, 4 on 1, ID Card Copy, Passport Copy		
SCAN				
Scan Type		Colour Contact	Image Sensor	
Scan Resolution	Optical	Platen glass: up to 600 x 600dpi, Feeder: up to 300 x 300dpi		
3Cull Resolution	Driver Enhanced	Up to 9 600 x 9 600 dpi		
Maximum Scan Size	Platen Glass	up to 216.0 x 297mm		
Maximum Scan Size	Feeder	up to 216.0 x 355.6mm		
Color Depth		24-bit		
Duplex Scan		Yes		
Pull Scan		Yes, USB and Network		
Push Scan (Scan To PC) with MF Scan Utility		Yes, USB and Network		
Scan to USB (via USB Host 2.0)		Yes		
Scan Driver Compatibility		TWAIN, WIA		
Scan Speed(*1)		1-Sided: 26.1 images/min (mono), 13.3 images/min (colour), 2-Sided: 51.2 images/min (mono), 26.1 images/min (colour)		
Scan to Cloud		MF Scan Utility		
SEND				
Sending Method		SMB, Email, FTP, IFAX Simple		
Color Mode		Full Colour, Grayscale, Monochrome		
Scan Resolution		300 x 600 dpi		
File Format		JPEG, TIFF, PDF, Compact PDF, PDF (OCR)		
FAX				
Modem Speed		Up to 33.6 Kbps		
Fax Resolution		Up to 408 x 392 dpi		
Compression Method		MH, MR, MMR, JBIG		
Memory Capacity(*2)		Up to 512 pages		
Favourite Dials (in address book)		19 diats		
Speed Dial (Coded Dial)		Up to 281 dials		
Group dials / Destinations		Max. 299 dials / Max. 299 destinations		
Sequential Broadcast		Max 310 destinations		
Duplex Fax (Transmission)		Yes		
Receive Mode		Fax Only, Manual, Answering, Fax/Tel Auto Switch		
Memory Backup		Permanent fax memory backup. (Backup with flash memory)		
Fax Features		Fax Forwarding, Dual Access, Remote Reception, PC Fax (Transmission only),		
		DRPD, ECM, Auto Redial, Fax Activity Reports, Fax Activity Result Reports, Fax Activity Management Reports		
Transmission Time		Approx. 2.6 s		

SPECIFICATIONS				
		MF645Cx	MF746Cx	
PAPER HANDLING				
Duplex Auto Document Feeder (DADF)		50 sheets (80g/m²)		
Available Paper Size for ADF		A4, B5, A5, Letter, Legal, Statement (min. 139,7 x 128.0 mm to max. 216.0 x 355.6 mm)		
Paper Input	Cassette	250 sheets		
	Multi-Purpose Tray	1 sheet	50 sheet	
	Optional Paper Feeder	N/A	550 sheets	
Maximum Paper Input Capacity		251 sheets	850 sheets	
Paper Output		100 sheets	150 sheets	
Paper Size	Cassette	A4, B5, A5, Letter, Legal, Statement, Executive, Government Letter, Government Legal, Foolscap, Indian Legal, Custom (Min. 76.2 x 127.0mm to Max. 216.0 x 355.6mm)	A4, B5, A5, Letter, Legal, Statement, Executive, Government Letter, Government Legal, Foolscap, Indian Legal, Custom (Min. 98.0 x 148.0mm to Max. 216.0 x 355.6mm)	
	Multi-Purpose Tray	A4, B5, A5, Letter, Legal, Statement, Executive, Government Letter, Government Legal, Foolscap, Indian Legal, Index Card Envelope: COM10, Monarch, C5, DL Custom (Min. 76,2 x 127,0mm to Max. 216.0 x 355.6mm)		
	Optional Paper Feeder	N/A	A4, B5, A5, Letter, Legal, Statement, Executive, Government Letter, Government Legal, Foolscap, Indian Legal Custom (Min., 98.0 x 148.0mm to Max. 216.0 x 355.6mm)	
Paper Types		Plain, Thick, Coated, Recycled, Colour, Label, Postcard, Envelope		
	ADF	50 to 105g/m²		
Paper Weight	Cassette / Optional Paper Feeder	60 to 200g/m²		
	Multi-Purpose Tray	60 to 200g/m²		
CONNECTIVITY & SOFTWARE				
	Wired	USB 2.0 High Speed, 10Base-T//100Base-TX/1000Base-T		
Standard Interface	Wireless	WFF1 802.11b/g/n (Infrastructure mode, WPS easy Setup, Direct Connection)		
Near Field Communication (NFC)		(Initiastracture mode, was easy serup, birect Connection)  N/A  Yes (Passive)		
	Print	LPD, RAW, WSD-Print (IPv4,IPv6)		
Network Protocol	Scan	Email, SMB, WSD-Scan(IPv4, IPv6), FTP		
Network Protocol	TCP/IP Application Services	Bonjour(mDNS), HTTP, HTTPS, POP before SMTP (IPv4,IPv6), DHCP, ARP+PING, Auto IP, WINS (IPv4), DHCPv6 (IPv6)		
	Management	SNMPv1, SNMPv3 (IPv4,IPv6)		
Nahuark Casurity	Wired	IP/Mac address filtering, HTTPS, SNMPv3, IEEE802,1x, IPSEC		
Network Security Wireless		WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (AES)		
One-Push Wireless Configuration		Wi-Fi Protected Setup (WPS)		
Other Features		Department ID, Secure Print, Application Library		
Mobile Solution		Canon PRINT Business, Canon Print Service, Google Cloud Print™, Apple® AirPrint®, Mopria® Print Service		
Address Book		LDAP		
Compatible Operating Systems(*3)		Windows® 10, Windows® 8.1, Windows® 7, Windows Server® 2016, Windows Server® 2012 R2, Windows Server® 2012, Windows Server® 2008, Mac® OS X 10.9.5 & up (*4), Linux (*4)		
Software Included		Printer driver, Fox driver, Scan Utility, Toner Status		
GENERAL				
Device Memory		1 GB		
LCD Display		WVGA Colour LCD 5.0° Touch Screen Display		
Dimensions (W x D x H)		451 x 460 x 413 mm	471 x 469 x 460 mm	
Weight		20.5 kg	24.5 kg	
Power Consumption (Maximum)		850 W or less	1 370 W or less	
Power Consumption (Average; During Operation)		Approx. 370 W	Approx. 530 W	
Power Consumption (Average; During Standby)		Approx. 11 W	Approx. 18.0 W	
Power Consumption (Average:		Approx. 0.8 W (USB/ LAN / Wi-Fi)	Approx. 0.7 W (USB/ LAN / Wi-Fi)	
Noise Levels(*5)  Operating Environment	During Operation	Sound Pressure Level: 51 dB, Sound Power Level: 69.4 B	Sound Pressure Level: 49 dB, Sound Power Level: 70.5 dB	
	During Standby	Sound Pressure Level: Inaudible, Sound Power Level: 43 dB	Sound Pressure Level: 26 dB, Sound Power Level: 43 dB	
	Temperature	10-30°C		
	Humidity	20% - 80% RH (no condensation)		
Power Requirements		AC 220 - 240 V(+/- 10%) , 50/60 Hz(+/- 2 Hz)		
Toner Cartridge(*6)	Standard	Cartridge 054 BK: 1 500 pages (bundled: 1 500 pages) Cartridge 054 C/M/Y: 1 200 pages (bundled: 680 pages) Cartridge 054H BK: 3 100 pages	Cartridge 055 BK: 2 300 pages (bundled: 2 300 pages) Cartridge 055 C/M/Y: 2 100 pages (bundled: 1 200 pages) Cartridge 055H BK: 7 600 pages	
	High	Cartridge 054H C/M/Y: 2 300 pages	Cartridge 055H C/M/Y: 5 900 pages	
Monthly Duty Cycle(*7)		30 000 pages	50 000 pages	
OPTIONAL ACCESSORIES				
Paper Feeder		N/A	Cassette Feeding Unit-AF1 (550 sheets)	
Barcode Printing		Barcode Printing Kit-E1		
Attachment Kit for NT-Ware Mi-Card Reader		Mi-Card Attachment Kit-B1		

- \*1 Speed of scanning via the document feeder, A4 size, scan resolution 300 x 300 dpi.
  \*2 Based on ITU-T #1 Chart ( standard mode).
  \*3 ScanGear is not available for Windows Server 2003/2008/2012.
  \*4 The latest drivers for Mac OS and Linux can be downloaded from the https://asia.canon website when available. Only the print function is supported for Linux.
- \*5 Tested in accordance to ISO 7779 and declared per ISO 9296.
- \*6Toner cartridge yield is in accordance with ISO/IEC 19798.
- o to the cultilidegree yield is in Accordance with 1807tet 1979.
  77 Monthly Duty Cycle value provides a means of comparison for product robustness in relation to other Canon multi-function laser devices, and does not refer to actual maximum image output per month.



### Canon India Pvt. Ltd.

7th Floor, Tower B, Building #5, DLF Epitome Building, DLF Phase III, Gurugram-122002Ph.: 0124-4160000 | Fax: 0124-4160011 | Web: in.canon