



High-Performance Wireless Ink Tank Printer for Small Businesses

The MAXIFY GX4070 makes your business look its best. Offering remarkable productivity for small work teams, this 4-in-1 inkjet printer provides ultra-affordable*¹⁰ colour printing and a wide range of connectivity options.

 **UP TO 21 000*¹⁰**
COLOUR PAGES

 **UP TO 9 000*¹⁰**
MONO PAGES
Economy Mode*¹¹

 **100
250**
PLAIN PAPER
CAPACITY

 **35**
SHEET ADF

 **3-WAY
PAPER FEEDING**

 **6.858 CM (2.7") TOUCH**

 **FAX**

 **CONNECTIVITY**

HIGHLIGHTER & WATER RESISTANT PRINTS

The quick-drying pigment ink ensures high-quality document printouts that resist fading or moisture and accidental exposure to water.

EASY MAINTENANCE


The easy-to-replace maintenance cartridge makes maintenance fuss-free and extends printer lifespan even when printing in high volumes.

FULL NETWORK COMPATIBILITY

Wireless and Wired LAN connectivity enhances installation flexibility. Print wirelessly and connect to smart devices directly.

COMPACT, SPACE SAVING FOOTPRINT

The printer's compact footprint allows it to fit into tight spaces with ease.



SPECIFICATIONS / MAXIFY GX4070

PRINT	Maximum Printing Resolution			600 (horizontal) x 1 200 (vertical) dpi
	Print Speed ¹ (Mono/Colour)	ESAT/Simplex		18 / 13 images per minute
		ESAT/Duplex		10 / 8 images per minute
		FPOT Ready/Simplex		8 / 9 s
Auto 2-Sided Printing (not applicable for Rear Flat Tray)				Yes
SCAN ²	Scanner Type			Flatbed (ADF / Platen)
	Scanning Method			Contact Image Sensor (CIS)
	Optical Resolution ³			1 200 x 2 400 dpi
	Maximum Document Size	Flatbed		A4, LTR (216 x 297 mm)
ADF		A4, LTR, LGL		
COPY	Copy Speed ⁴	Colour	sFCOT/ Simplex	11.1 images per minute
			sESAT/ Simplex	17 s
		ADF (Mono/ Colour)	ESAT/ Simplex	15.2 / 7.4 images per minute
	Maximum Copies			99 pages
Maximum Document Size			A4, LTR	
FAX	Transmission Speed ⁵	Mono/Colour		3 s / 1 min
	Transmission/Reception Memory ⁶			250 pages
	PC Fax			Windows: Available, Mac: Available
	Automatic Dialing	Coded Speed Dialing (max.)		100 locations
Group Dialing (max.)		99 locations		
PAPER HANDLING	Maximum Input Capacity	Rear Tray	Plain Paper 64 g/m ² (gsm)	Up to 100 sheets
		Cassette	Plain Paper 64 g/m ² (gsm)	Up to 250 sheets
		Rear Flat Tray	Paperboard	1 sheet
		ADF	Plain Paper 64 g/m ² (gsm)	A4, LTR: 35 sheets, LGL: 5 sheets
	Media Size	Rear Tray	A4, A5, A6, B5, LTR, LGL, Foolscap, FS, Envelope (COM10, DL, C5, Monarch), Card Size (91 x 55 mm), 101.6 x 152.4 mm (4x6"), 127 x 177.8 mm (5x7") 177.8 x 254 mm (7x10"), 203.2 x 254 mm (8x10") Square (127 x 127 mm), Custom (width: 89 – 216 mm, length: 127 – 1 200 mm)	
		Cassette	A4, A5, B5, LTR, Executive, Custom (width: 148 – 215.9 mm, length: 210 – 297 mm)	
		Rear Flat Tray	A4, B5, LTR, Custom (width: 89 – 215.9 mm, length: 127 – 1 200 mm)	
	Auto 2-sided Printing		A4, LTR	
	Media Type	Rear Tray	Plain Paper 64 – 105 g/m ² (gsm) High Resolution Paper (HR-101N) Photo Paper Plus Glossy II (PP-201/PP-208) Glossy Photo Paper (GP-508) Photo Paper Plus Semi-Gloss (SG-201) Photo Paper Pro Luster (LU-101) Matte Photo Paper (MP-101) Double-Sided Matte Paper (MP-101D) Photo Stickers (PS-208/PS-808) Envelope	
			Cassette	Plain Paper 64 – 105 g/m ² (gsm)
		Rear Flat Tray	Paperboard (thickness: 0.1 – 0.7 mm)	

NETWORK SYSTEM REQUIREMENTS & GENERAL SPECIFICATIONS	Operating System Compatibility	Please visit https://asia.canon.to to confirm OS compatibility and to download the latest drivers.		Windows 11 / 10 / 8.1 / 7 SP1 ¹⁷ macOS 10.14.16 – 12 or later Chrome OS
	Connectivity	Network		Wireless LAN IEEE802.11b/g/n/a ¹⁸ /ac ¹⁸ Wired LAN 100 Base-TX/10 Base-T
		Interface		USB 2.0
	Canon Printing Apps	Mobile		Canon PRINT Inkjet/SELPHY, Easy-PhotoPrint Editor, Creative Park
		Others		Easy Layout Editor, PosterArtist Lite, PosterArtist (Web), Canon Inkjet Smart Connect
	Mobile/Cloud Printing Solutions		AirPrint, Mopria, Canon Print Service (Android), Direct Wireless, MAXIFY Cloud Link	
	Power		AC 100 – 240 V, 50/60 Hz	
	Power Consumption ⁹		20 W (Standby: 0.9 W)	
	Duty Cycle		Up to 33 000 pages/month	
	Recommended Monthly Print Volume		300 – 2 500 pages	
CONSUMABLES	Operation Panel	Display	6.7 cm (2.7 in) LCD (Touch Screen, Colour)	
	Dimensions (WxDxH)	Factory Configuration		399 x 417 x 251 mm
		Output/ADF Trays Extended		399 x 719 x 304 mm
	Weight		9.5 kg	
	Ink Bottles	Type/Colours		All Pigment Inks / Black, Cyan, Magenta, Yellow
		Page Yield ¹⁰		GI-76 PGBK: 6 000 (Standard) / 9 000 (Economy ¹¹) GI-76 PG C, M, Y: 14 000 ¹² (Standard) / 21 000 ¹² (Economy ¹¹)
	User Replaceable Maintenance Cartridge		MC-G03	

Specifications are subject to change without notice.

- Document print speeds are the averages of ESAT (Word, Excel, PDF) in Office Category Test for the default simplex mode, ISO/IEC 24734. Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.
- TWAIN driver (ScanGear) is based on the TWAIN specification V1.9 and requires the Data Source Manager comes with the operating system.
- Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard. Optical resolution scan is available, only when you use TWAIN Driver.
- Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183. Copy speeds (ADF) are ESAT of copy in sequence, ISO/IEC24735. Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warm up time.
- Black & white document fax transmission speed is based on default setting using ITU-T No. 1 chart. Colour document fax transmission speed is based on default setting using Canon Colour Fax Test Sheet. Actual transmission speed may vary depending on document complexity, fax settings at receiving end, and line conditions etc.
- Page count is based on ITU-T No. 1 chart or Canon FAX Standard Chart No. 1.
- Operation can only be guaranteed on a PC with a pre-installed Windows 7 or later.
- Wireless LAN IEEE802.11a/ac are available for Taiwan models only.
- When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings.
- The page yield is based on the consumption data from the succeeding ink bottle but not the first ink bottle. Page yield is the estimated value based on Canon individual test method using the ISO/IEC 24712 chart under ideal print conditions & continuous printing simulation with the replacement after initial setup. Mentioned print yield is from the replacement set of 6-ink bottles (GY/C/M/Y/R/BK) & each bottle contains 60ml of ink. Page yield varies significantly depending on contents printed and other factors. MRP of Black ink bottle is INR 622 and each colour ink bottle is INR 622 inclusive of all tax.
- The Economy mode reduces the ink consumption by lowering the density. More pages can be printed by using this mode.
- Based on 1 set of colour bottles.



Canon India Pvt. Ltd.

Corporate Office: 7th Floor, Tower B, Building #5, DLF Epitome Building, DLF Phase III, Gurugram-122002
Ph: 0124-4160000 | Fax: 0124-4160011 | Web: in.canon

DEALER'S STAMP

This document is for information purpose only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.