



Refillable Ink Tank Printer with Low-Cost Ink Bottles

This high-performance printer combines low-cost*⁵ printing with easy operation and maintenance, alongside being compatible with low-cost*⁵ ink bottles for greater cost efficiency.

UP TO
8100*⁵
COLOUR PAGES

UP TO
7600*⁵
MONO PAGES
Economy Mode*⁶



REFILLABLE INK TANK PRINTER
WITH LOW-COST*⁵ INK BOTTLES

LOW-COST*⁵ INK BOTTLES

Small and standard ink bottles are available to meet the different requirements in print volume.

*Published highest yield is achievable based on Standard ink bottle and printing on Economy mode. For more details, refer to specifications on underside of leaflet.

EASY, HASSLE-FREE INK REFILLING

Ink refilling is now made easy. Each ink bottle nozzle is designed to fit seamlessly only into the designated ink tank, eliminating potential mixing accidents.

EASY MAINTENANCE

The easy-to-replace maintenance cartridge makes maintenance fuss-free and extends the printer's lifespan even when printing in high volumes.

COMPACT, SPACE SAVING FOOTPRINT

The printer's compact footprint allows it to fit into tight spaces with ease.



SPECIFICATIONS / PIXMA G1730			
PRINT	Maximum Printing Resolution ¹		4 800 (horizontal) x 1 200 (vertical) dpi
	Print Speed ²	ESAT/Simplex (Mono/Colour)	11 / 6 images per minute
		FPOT Ready/Simplex (Mono/Colour)	9 / 14 s
		Photo 101.6 x 152.4 mm (4x6")	45 s
PAPER HANDLING	Maximum Input Capacity	Plain Paper (64 g/m ² (gsm))	Up to 100 sheets
		Photo Paper 101.6 x 152.4 mm (4x6")	Up to 20 sheets
	Media Size		A4, A5, A6, B5, LTR, LGL, Executive, Legal, Foolscap, F4, Oficio2, B-Oficio, M-Oficio, Envelope (COM10, DL, C5, Monarch), Card Size (91 x 55 mm), 101.6 x 152.4 mm (4x6"), 127 x 177.8 mm (5x7"), 177.8 x 254 mm (7x10"), 203.2 x 254 mm (8x10"), Square (89 x 89 mm, 127 x 127 mm), Custom (width: 55 – 216 mm, length: 89 – 1 200 mm)
	Media Type		Plain Paper (64 – 105 g/m ² (gsm)) High Resolution Paper (HR-101N) Photo Paper Plus Glossy II (PP-201, PP-208) Glossy Photo Paper (GP-508) Photo Paper Plus Semi-Gloss (SG-201) Photo Paper Pro Luster (LU-101) Matte Photo Paper (MP-101) Double-Sided Matte Paper (MP-101D) Photo Stickers (PS-208/PS-808) Envelope
SYSTEM REQUIREMENTS & GENERAL SPECIFICATIONS	Operating System Compatibility	Please visit https://asia.canon/support to confirm OS compatibility and to download the latest drivers.	Windows 11 / 10 / 8.1 / 7 SP1 ³ macOS 10.14.6 – 12 or later Chrome OS
	Interface		USB 2.0
	Power		AC 100 – 240 V, 50 / 60 Hz
	Power Consumption ⁴		14 W (Standby: 0.6 W)
	Duty Cycle		Up to 3 000 pages/month
	Recommended Monthly Print Volume		150 – 1 500 pages
	Dimensions (W x D x H)	Factory Configuration	416 x 330 x 146 mm
		Output/Trays Extended	416 x 557 x 267 mm
	Weight		4.6 kg
CONSUMABLES	Ink Bottles	Type/Colours	Pigment Ink / Black Dye-Based Ink / Cyan, Magenta, Yellow
		Print Yield ⁵ (Plain Paper: A4, Prints)	GI-71 PGBK: 6 000 (Standard) / 7 600 (Economy ⁶) GI-71 C, M, Y: 7 700 (Standard) / 8 100 (Economy ⁶) GI-71S PGBK: 3 100 (Standard) / 3 900 (Economy ⁶) GI-71S C, M, Y: 4 400 (Standard) / 4 600 (Economy ⁶)
		Print Yield ⁵ (Photo Paper, PP-201: 101.6 x 152.4 mm (4 x 6"), Sheets)	GI-71 PGBK: NA ⁷ GI-71 C, M, Y: 2 200 GI-71S PGBK: NA ⁷ GI-71S C, M, Y: 1 200
	User Replaceable Maintenance Cartridge		MC-G04

Specifications are subject to change without notice.

¹ Ink droplets can be placed with a pitch of 1/4800 inch at minimum.

² Document print speeds are the averages of ESAT (Word, Excel, PDF) in Office Category Test for the default simplex mode, ISO/IEC 24734. Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.

³ Operation can only be guaranteed on a PC with a pre-installed Windows 7 or later.

⁴ When printing ISO/JIS-SCID N2 on A4 size plain paper using default settings.

⁵ The page yield is based on the consumption data from the succeeding ink bottle but not the first ink bottle. Page yield is the estimated value based on Canon individual test method using the ISO/IEC 24712 chart under ideal print conditions & continuous printing simulation with the replacement after initial setup. Mentioned print yield is from the replacement set of 6-ink bottles (GY/C/M/Y/R/BK) & each bottle contains 60ml of ink. Page yield varies significantly depending on contents printed and other factors. MRP of Black ink bottle GI 71 is INR 488 and GI 71s is INR 314. MRP of each colour ink bottle GI 71 is INR 422 and GI 71s is INR 292 inclusive of all tax.

⁶ The Economy mode reduces the ink consumption by lowering the density. More pages can be printed than the standard mode.

⁷ Black ink is not used when printing under this condition. However, a minimal amount of black ink is used for maintenance purpose.



Canon India Pvt. Ltd.

Corporate Office: 7th Floor, Tower B, Building #5, DLF Epitome Building, DLF Phase III, Gurugram-122002
Ph.: 0124-4160000 | Fax: 0124-4160011 | Web: in.canon

DEALER'S STAMP

This document is for information purpose only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.