



Wireless Refillable Ink Tank Printer with Fax for Low-Cost Printing

Enjoy the convenience of wireless printing and high-productivity with the PIXMA G4770. This 4-in-1 printer features a 35-sheet Auto Document Feeder for batch scanning productivity.

UP TO
8,100*
COLOUR PRINTS

UP TO
7,600*
MONO PRINTS
*Economy Mode

1.35"
(3.4cm)
LCD

3.4CM LCD

CONNECTIVITY


EASY, HASSLE-FREE INK REFILL

Ink refilling is now made easy. Each ink bottle nozzle is designed to fit seamlessly only into the designated ink tank, eliminating potential mixing accidents.



EASY MAINTENANCE

The easy-to-replace maintenance cartridge makes maintenance fuss-free and extends the printer's lifespan even when printing in high volumes.



AUTO DOCUMENT FEEDER

Up to 35 sheets of document originals can be loaded for batch scanning and copying, eliminating the need for repeated opening and closing of the scanner lid.



MOBILE AND CLOUD PRINTING

Print from smartphones, tablets, laptops and cloud storage with the Canon PRINT Inkjet/SELPHY and Easy-PhotoPrint Editor apps.



SPECIFICATIONS				PIXMA G4770	
PRINT	Maximum Printing Resolution			4,800 (horizontal) ¹ x 1,200 (vertical) dpi	
	Print Speed ²	ESAT/Simplex (Mono/Colour)		11 / 6 images per minute	
		FPOT Ready/Simplex (Mono/Colour)		9 / 14 s	
		Photo (4 x 6")		45 s	
SCAN ³	Scanner Type			Flatbed (ADF / Platen)	
	Scanning Method			Contact Image Sensor (CIS)	
	Optical Resolution ⁴			600 x 1,200 dpi	
	Maximum Document Size	Flatbed		A4, LTR (216 x 297 mm)	
ADF		A4, LTR, LGL			
COPY	Copy Speed ⁵	Colour	sFCOT/Simplex	23 s	
			sESAT/Simplex	3.2 images per minute	
		ADF (Colour)	ESAT/Simplex	1.8 images per minute	
	Maximum Copies			99 prints	
	Maximum Document Size			A4, LTR	
FAX	Transmission Speed ⁶	Mono/Colour		3 s/ 1 min	
	Transmission/Reception Memory ⁷			50 prints	
	PC Fax			Windows: Available, Mac: Available	
	Automatic Dialing	Coded Speed Dialing (max.)		20 locations	
		Group Dialing (max.)		19 locations	
PAPER HANDLING	Maximum Input Capacity	Rear Tray	Plain Paper (64 g/m²)	Up to 100 sheets	
			Photo Paper (4 x 6")	Up to 20 sheets	
		ADF	Plain Paper (64 g/m²)	A4, LTR: 35 sheets, LGL: 5 sheets	
	Media Size	Rear Tray		A4, A5, A6, B5, LTR, LGL, Executive, Legal, Foolscap, F4, Oficio2, B-Oficio, M-Oficio, Envelope (COM10, DL, C5, Monarch), Card Size (91 x 55 mm), 4 x 6", 5 x 7", 7 x 10", 8 x 10", Square (89 x 89 mm, 127 x 127 mm), Custom (width: 55 – 216 mm, length: 89 – 1,200 mm)	
	Media Type	Rear Tray		Plain Paper (64 – 105 g/m²) High Resolution Paper (HR-101N) Photo Paper Plus Glossy II (PP-201, PP-208) Glossy Photo Paper (GP-508) Photo Paper Plus Semi-Gloss (SG-201) Photo Paper Pro Luster (LU-101) Matte Photo Paper (MP-101) Double-Sided Matte Paper (MP-101D) Photo Stickers (PS-208, PS-808) Envelope	
NETWORK SYSTEM REQUIREMENTS & GENERAL SPECIFICATIONS	Operating System Compatibility	Please visit https://asia.canon to confirm OS compatibility and to download the latest drivers.		Windows 11 / 10 / 8.1 / 7 SP1 ⁸ macOS 10.14.16 – 12 or later Chrome OS	
	Interface			Wireless LAN IEEE802.11b/g/n/a/ac ⁹ USB 2.0	
	Canon Printing Apps	Mobile		Canon PRINT Inkjet/SELPHY, Easy-PhotoPrint Editor, Creative Park	
		Others		Easy Layout Editor, PosterArtist Lite, PosterArtist (Web), Canon Inkjet Smart Connect	
	Mobile/Cloud Printing Solutions			AirPrint, Mopria, Canon Print Service (Android), Direct Wireless PIXMA Cloud Link	
	Power			AC 100 – 240 V, 50/60 Hz	
	Power Consumption ¹⁰			15 W (Standby: 0.6 W)	
	Duty Cycle			Up to 3,000 Prints/month	
	Recommended Monthly Print Volume			150 – 1,500 Prints	
	Operation Panel	Display		1.35" / 3.4 cm LCD (Monochrome)	
	Dimensions (W x D x H)	Factory Configuration		416 x 337 x 212 mm	
		Output/ADF Trays Extended		416 x 556 x 268 mm	
Weight			7.2 kg		
CONSUMABLES	Ink Bottles	Type/Colours		Pigment Ink / Black Dye-Based Ink / Cyan, Magenta, Yellow	
		Print Yield ¹¹ (A4, Prints)		GI-71 PGBK: 6,000 (Standard) / 7,600 (Economy) ¹³ GI-71 C, M, Y: 7,700 ¹² (Standard) / 8,100 ¹² (Economy) ¹³	
	User Replaceable Maintenance Cartridge			MC-G04	

Specifications are subject to change without notice.

¹ Ink droplets can be placed with a pitch of "0.000529 cm (1/4800 inch)" at minimum.

² Document print speeds are the averages of ESAT (Word, Excel, PDF) in Office Category Test for the default simplex mode, ISO/IEC 24734. Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer.

Print speed may vary depending on system configuration, interface, software, document complexity, print mode, Print coverage, type of paper used etc.

³ TWAIN driver (ScanGear) is based on the TWAIN specification V1.9 and requires the Data Source Manager comes with the operating system.

⁴ Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard. Optical resolution scan is available only when you use TWAIN Driver.

⁵ Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183. Copy speeds (ADF) are ESAT of copy in sequence, ISO/IEC24735. Copy speed may vary depending on document complexity, copy mode, Print coverage, type of paper used etc. and does not take into account warm up time.

⁶ Black & white document fax transmission speed is based on default setting using ITU-T No. 1 chart. Colour document fax transmission speed is based on default setting using Canon Colour Fax Test Sheet. Actual transmission speed may vary depending on document complexity, fax settings at receiving end, and line conditions etc.

⁷ Print count is based on ITU-T No.1 chart or Canon FAX Standard Chart No. 1.

⁸ Operation can only be guaranteed on a PC with a pre-installed Windows 7 or later.

⁹ Wireless LAN IEEE802.11a/ac are available for the Taiwan models only.

¹⁰ When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings.

¹¹ The Print yield (A4 size) is based on the consumption data from the succeeding ink bottle but not the first ink bottle. Print yield is the estimated value based on Canon individual test method using the ISO/IEC 24712 chart under ideal print conditions & continuous printing simulation with the replacement after initial setup. Mentioned print yield is from the replacement set of 4-ink bottles (C/M/Y/BK). Black bottle contains 135ml ink and each colour bottle contains 70ml of ink. Print yield varies significantly depending on contents printed and other factors.

¹² Based on 1 set of colour bottles.

¹³ The Economy mode reduces the ink consumption by lowering the density. More Prints can be printed by using this mode.



CANON INDIA PVT. LTD.

Corporate Office: 7th Floor, Tower B, Building #5, DLF Epitome Building, DLF Phase III, Gurugram-122002
Ph.: 0124-4160000 | Fax: 0124-4160011 | Web: in.canon

DEALER'S STAMP

This document is for information purposes only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.