

PIXMA TR160
PIXMA TR160 with battery

Canon
Delighting You Always



Built for **Business**

Wireless Mobile Printer for On-the-Go Professionals

Designed for ultimate portability and performance, this wireless mobile printer features an intuitive 3.7cm (1.44") OLED display for easy wireless setup and operation. Print directly from smartphones and store customised forms on the device, and support USB Charging*, making it the ideal choice for professionals on the go.

3.7cm
(1.44")
OLED

3.7 CM
(1.44") OLED

MOBILE DEVICE
PRINTING

2.4GHz/5GHz
DUAL BAND

USB CHARGE*

BATTERY
ATTACHMENT

ANTI-THEFT
LOCK SLOT

*USB charging is supported only with the external battery.

DIRECT PRINTING

Print directly using pre-loaded customised forms or from connected mobile phones, offering both flexibility and convenience for professionals on the move.



HIGH-CONTRAST OLED DISPLAY

Easily monitor ink levels and Wi-Fi signal strength at a glance, ensuring uninterrupted printing and a seamless connection for maximum productivity.



REMOVABLE BATTERY

USB Charging* is supported through laptops, power banks, or USB wall chargers, ensuring readiness to print anywhere, anytime.



10-MIN BOOST CHARGE

Up to 36 pages of printing performance are delivered with just a 10-minute quick charge, ensuring reliability for urgent tasks.



IMAGING **POSSIBILITIES & BEYOND**

SPECIFICATIONS				PIXMA TR160 / TR160 with battery
PRINT	Maximum Printing Resolution		4 800 (horizontal) ^{*1} x 1 200 (vertical) dpi	
	Print Speed ^{*2} (approx.)	ESAT/Simplex (Mono/Colour)		9.0 / 5.5 images/min
		FPOT Ready/Simplex (Colour)		15 s
		Photo (4 x 6" Borderless)		53 s
PAPER HANDLING	Maximum Input Capacity	Rear Tray	Plain Paper (64 g/m ²)	Up to 50 sheets
			Photo Paper (4 x 6")	Up to 20 sheets
	Media Size	Rear Tray		A4, A5, B5, LTR, LGL, 4 x 6", 5 x 7", 7 x 10", 8 x 10", Square (89 X 89 mm, 127 x 127 mm), Card Size (91 x 55 mm), Envelope (COM10, DL), Custom size (width: 55 - 215.9 mm, length: 89 - 676 mm)
		Borderless Printing ^{*3}		A4, LTR, 4 x 6", 5 x 7", 7 x 10", 8 x 10", Square (89 x 89 mm, 127 x 127 mm), Card Size (91 x 55 mm)
	Media Type	Rear Tray		Plain Paper (64 - 105 g/m ²) High Resolution Paper (HR-101N) Photo Paper Plus Glossy II (PP-201, PP-208) Matte Photo Paper (MP-101) Double-Sided Matte Paper (MP-101D) Envelope
NETWORK SYSTEM REQUIREMENTS & GENERAL SPECIFICATIONS	Operating System Compatibility		Please visit https://asia.canon/support to confirm OS compatibility and to download the latest drivers.	
	Connectivity	Network		Wireless LAN IEEE 802.11a/ac/b/g/n
		Wi-Fi Frequency		2.4 GHz / 5 GHz
		Interface		USB 2.0
	Canon Printing Apps	Mobile (iOS/Android)		Canon PRINT, Easy-PhotoPrint Editor, Creative Park
		PC (Windows/Mac)		Canon PRINT, Easy-PhotoPrint Editor, Easy-Layout Editor (Win only), PosterArtist Lite (Win only), PosterArtist Web (browser-based)
	Mobile/Cloud Printing Solutions		AirPrint®, Mopria® Print Service, Canon Print Service (Android), Direct Wireless, Cloud Integration Service (via smartphone/tablet)	
	Power		AC 100 - 240 V, 50/60 Hz	
	Power Consumption ^{*5} (approx.)		8 W (Standby: 1.1 W)	
	Recommended Monthly Print Volume		10 - 80 prints	
	Operation Panel	Display		3.7cm (1.44") / 3.6 cm (1.41") OLED (Mono)
	Dimensions (W x D x H) (approx.)		322 x 185 x 66 mm / 322 x 210 x 66 mm (with battery)	
	Weight (approx.)		2.1 kg / 2.3 kg (with battery)	
CONSUMABLES	Ink Cartridges	Type/Colours		Pigment Ink / Black Dye-Based Ink / Colour
		Page Yield ^{*6}	Plain Paper	A4 Colour Documents ^{*7} PGI-35: 200 CLI-36: 260
			Photo Paper (PP-208)	4 x 6" Photos ^{*8} PGI-35: N/A CLI-36: 102
ACCESSORY	External Battery, LK-72 (Optional for TR160; bundled for TR160 with battery)	Type		Lithium-ion
		Voltage Level		DC 10.8V; 2170 mAh
		Charging Time (approx.)	AC Adaptor	2 hr 20 min
			USB 1.5A	5 hr
		Printable Pages (approx.)	Full charge ^{*9}	330 sheets
			10 min charge with AC Adaptor ^{*10}	36 sheets
			5 min charge with USB 1.5A ^{*10}	4 sheets

Specifications are subject to change without notice. For detailed specifications, please refer to product information on <https://asia.canon>.

^{*1} Ink droplets can be placed with a pitch of 1/4800 inch at minimum.

^{*2} Document print speeds are the averages of ESAT (Word, Excel, PDF) in Office Category Test for the default simplex mode, ISO/IEC 24734.

Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.

^{*3} Paper types NOT supported for borderless printing are as follows: Envelope, High Resolution Paper, T-Shirt Transfer, Photo Stickers.

^{*4} Operation can only be guaranteed on a PC with a pre-installed Windows 7 or later.

^{*5} When printing ISO/JIS-SCID N2 on A4 size plain paper using default settings.

^{*6} Page yields may vary depending on content coverage, print settings, temperature, humidity, and frequency of printing.

^{*7} Declared yield value is in accordance with ISO/IEC 24711, using the ISO/IEC 24712 colour chart. Values obtained by continuous printing.

^{*8} Declared yield value is in accordance with ISO/IEC 29102, using the ISO/IEC 29103 chart. Values obtained by continuous printing. Black ink is not used when printing under this condition. However, a minimal amount of black ink is used for maintenance purposes.

^{*9} Tested under normal temperature and humidity conditions, using a fully charged new battery, printing ISO/IEC 24712 files (5 patterns) continuously in colour on A4 plain paper in the printer driver's Standard mode.

^{*10} Tested under normal temperature and humidity conditions, printing ISO/IEC 24712 files (5 patterns) continuously in colour on A4 plain paper in the printer driver's Standard mode, printed via USB connection without Wi-Fi connection.



CANON INDIA PVT. LTD.

7th Floor, Tower B, Building #5, DLF Epite Building, DLF Phase III, Gurugram-122002
Ph.: 0124-4160000 | Fax: 0124-4160011 | Web: in.canon

DEALER'S STAMP

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weight and dimensions are approximates. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.