

EOS 6D Mark II 5,00 incl. of all taxes



EOS 6D Mark II w/24-70 f4L IS USM kit: R. 184,995.00 incl. of all taxes



EOS 6D Mark II w/24-105 f4L IS II USM: R. 202,995.00 incl. of all taxes



Optional battery grip BG-E21: INR. 12,495.00 incl, of all taxes




Bluetooth Remote Controller BR-E1: INR, 2,595,00

visit https://edge.canon.co.in/EOS6DMarkII



Specifications



Type	Digital, single-lens reflex, AF/AE camera
Effective Pixels	Approx. 26.2 megapixels
Sensor type	Full-frame CMOS sensor, approx. 35.8 x 23.9mm
Continuous Shooting (approx.)	Max. 6.5 fps for approx. 19 shots RAW+JPEG (max size)
Image Processor	DIGIC 7
LCD	TFT colour, 7.7 cm/3.03 inch, 1,040,000 dot
Optical Viewfinder	Approx. 98% coverage, Approx. 0.71x magnification
Shutter Speed Range	1/4000sec. to 30sec., bulb, X-sync at 1/180sec.
Shooting Modes	Portrait, Group Photo, Landscape, Sports, Kids, Panning (New), Close-up, Food, Candlelight, Night Portrait, Handheld Night Scene, HDR Backlight Control
ISO Sensitivity	ISO 100 - 40000 (in 1/3 or 1 stop increments). Expandable to L (ISO 50), H1 (ISO 51200) & H2 (ISO 102400)
AF System / Points LCD	45-all cross type AF system, 27 points @ f/8.0
EOS Movie	1920 x 1080 (Full HD): 60p / 50p / 30p / 25p 1280 x 720 (HD): 60p / 50p / 30p / 25p
Connectivity	Built in Wi-Fi, NFC, Bluetooth & GPS
HDMI Mini Output	Yes
Memory Cards	SD, SDHC or SDXC memory card
Dimensions (WxHxD)	144,0 (W) x 110.5 (H) x 74,8 (D) mm
Weight (body only)	685 grams (CIPA), 765 grams w/ battery + SD Card

All the data above is based on Canon's testing standards and CIPA (Camera & Imaging Products Association) testing standards and guidelines.


Canon India Pvt.Ltd. Corporate Office: 7th & 8th Floor, Tower B, Building No. 5 DLF Epitome, DLF Phase III. Gurgaon -122002

For Canon Service Centers, call: Toll Free No.: 1800 180 3366/1800 208 3366 customersupport@canon.co.in

Canon Master Service Centers: Delhi, Kolkata, Mumbai, Bangalore, Chennai, Cochin **Canon Authorised Service franchise:**

Hyderabad, Cochin, Chennai, Bhubaneswar, Patna, Guwahati, Pune, Jaipur, Indore,

Canon Quick Repair Center:



Dealer Stamp

Disclaimer:
*All images and effects are simulated, actual images may vary. Models and specifications are subject to change without prior notification. Prices mentioned for all products are MRP (inclusive of all taxes) prices. Errors and omission expected. Wi-Fi is a trademark. Canon is a registered trademark of Canon Inc. Offer valid till stocks last. Wi-Fi support varies by region & device type. Uploading of the still images/videos to any website directly from Wi-Fi camera is subject to registration on Canon Image Gateway. Transfer of the still images/videos to iPhone/iPad/Android devices from Wi-Fi camera is subject to download of free app. Canon CameraWindow. Both NFC and Wi-Fi can be used to shoot remotely from an Android device, or even upload directly to social networking sites. Manual explains file transfer between camera and smartphone





0







EOS 6D Mark II 5.00 incl. of all taxes



EOS 6D Mark II w/24-70 f4L IS USM kit: R. 184,995.00 incl. of all taxes



Bluetooth Remote Controller



EOS 6D Mark II w/24-105 f4L IS II USM: R. 202,995,00 incl. of all taxes



Optional battery grip BG-E21: INR. 12,495.00 incl, of all taxes



BR-E1: INR. 2,595.00

Specifications



Туре	Digital, single-lens reflex, AF/AE camera
Effective Pixels	Approx. 26.2 megapixels
Sensor type	Full-frame CMOS sensor, approx. 35.8 x 23.9mm
Continuous Shooting (approx.)	Max. 6.5 fps for approx. 19 shots RAW+JPEG (max size)
Image Processor	DIGIC 7
LCD	TFT colour, 7.7 cm/3.03 inch, 1,040,000 dot
Optical Viewfinder	Approx. 98% coverage, Approx. 0.71x magnification
Shutter Speed Range	1/4000sec. to 30sec., bulb, X-sync at 1/180sec.
Shooting Modes	Portrait, Group Photo, Landscape, Sports, Kids, Panning (New), Close-up, Food, Candlelight, Night Portrait, Handheld Night Scene, HDR Backlight Control
ISO Sensitivity	ISO 100 - 40000 (in 1/3 or 1 stop increments). Expandable to L (ISO 50), H1 (ISO 51200) & H2 (ISO 102400)
AF System / Points LCD	45-all cross type AF system, 27 points @ f/8.0
EOS Movie	1920 x 1080 (Full HD): 60p / 50p / 30p / 25p 1280 x 720 (HD): 60p / 50p / 30p / 25p
Connectivity	Built in Wi-Fi, NFC, Bluetooth & GPS
HDMI Mini Output	Yes
Memory Cards	SD, SDHC or SDXC memory card
Dimensions (WxHxD)	144.0 (W) x 110.5 (H) x 74.8 (D) mm
Weight (body only)	685 grams (CIPA), 765 grams w/ battery + SD Card


All the data above is based on Canon's testing standards and CIPA (Camera & Imaging Products Association) testing standards and guidelines.

Canon India Pvt.Ltd. Corporate Office: 7th & 8th Floor, Tower B, Building No. 5 DLF Epitome, DLF Phase III. Gurgaon -122002

For Canon Service Centers, call: Toll Free No.: 1800 180 3366/1800 208 3366 customersupport@canon.co.in

Canon Master Service Centers: Delhi, Kolkata, Mumbai, Bangalore, Chennai, Cochin Canon Authorised Service franchise: Hyderabad, Cochin, Chennai, Bhubaneswar, Patna, Guwahati, Pune, Jaipur, Indore,

Canon Quick Repair Center:



Dealer Stamp

Disclaimer:
*All images and effects are simulated, actual images may vary. Models and specifications are subject to change without prior notification. Prices mentioned for all products are MRP (inclusive of all taxes) prices. Errors and omission expected. Wi-Fi is a trademark. Canon is a registered trademark of Canon Inc. Offer valid till stocks last. Wi-Fi support varies by region & device type. Uploading of the still images/videos to any website directly from Wi-Fi camera is subject to registration on Canon Image Gateway. Transfer of the still images/videos to iPhone/iPad/Android devices from Wi-Fi camera is subject to download of free app. Canon CameraWindow. Both NFC and Wi-Fi can be used to shoot remotely from an Android device, or even upload directly to social networking sites. Manual explains file transfer between camera and smartphone







AFI PMF

EF

CANON ZOOM LENS



The 26.2 megapixel full frame sensor provides incredible detail, depth and dynamic range to your photos bringing them to life with realistic textures and tonal detail.





With a standard ISO range of 100 to 40,000, get ready to rule the night with the EOS 6D Mark II. Create masterpieces in low light by dialing up the ISO without bothering about noise.





The 45-point all cross type point AF offers unparalleled focusing speed and accuracy along with advanced subject tracking in conjunction with Al Servo AFII. Enjoy unmatched flexibility with 27 points active at f/8.0


















DAF brings unmatched flexibility and performance with accurate and responsive live view focusing and subject tracking. Use DAF while using the LCD to capture photos, or in video mode to create artistic films. This works in conjunction with the touchscreen for flawless touch/focus/click capabilities.

The EOS 6D Mark II shoots at a continuous speed of 6.5 frames per second, which is fast enough for action sports, wildlife and wedding photography, ensuring you never miss a moment.









Create brilliant Time Lapse videos easily inside the camera with inbuilt time lapse movie mode. With the EOS 6D Mark II you can select between Full HD & 4K Ultra HD resolutions.





The new DIGIC 7 processor powers everything on the EOS 6D Mark II - from its auto focus, to light metering & image processing. Enjoy flicker free shooting, diffraction correction and many more advanced technologies powered by the latest DIGIC.



RGB+IR Metering 7,560-pixel RGB + IR metering sensor

DIGIC 7 image processor

The 7,560-pixel RGB + IR sensor allows the EOS 6D Mark II to shoot under even challenging light conditions and provide reliable results, with accurate metering to represent the truest possible depiction of the scene.



Vari angle LCD Touchscreen, articulating LCD

The articulating touchscreen makes usability a snap. Whether you're capturing still or video, the EOS 6D Mark II presents a seamless user interface that new users and veterans alike will greatly appreciate.



With inbuilt GPS capturing latitude, longitude and altitude, the EOS 6D Mark II is the camera of choice for the intrepid traveler.



At a mere 685 grams (765 grams including battery and card), the EOS 6D Mark II is lightweight and compact. It also features robust weather sealing against dust and moisture ingress to make it suitable for demanding professionals.









The EOS 6D Mark II presents all possible connectivity options and will tether with your smartphone and other wireless devices allowing remote control, image transfer, upload to social networking sites, wireless printing and more.