

Canon

Delighting You Always

CINEMA EOS SYSTEM RF CINEMA LENS



**CINEMA EOS
SYSTEM**



CINEMA EOS SYSTEM

RF CINEMA LENS



Professionally crafted lenses by Canon, for the motion film industry.
Creating your ideas and stories.



CN-R14mm T3.1 L F • CN-R20mm T1.5 L F • CN-R24mm T1.5 L F • CN-R35mm T1.5 L F • CN-R50mm T1.3 L F • CN-R85mm T1.3 L F • CN-R135mm T2.2 L F

NEW DISTORTION CORRECTION

*Supported cameras: EOS C70,
and EOS R5 C (Movie Mode only)

High speed data transfer makes it possible for instant
transfer of lens metadata to the camera



Lines are straightened



Lines look distorted

EOS-LENS COMMUNICATION SUPPORT

The 12-pin electronic contacts also improve lens-camera communication speed and enable new functions.



Lens metadata can be read, recorded, and displayed at the destination site

DIRECT RF MOUNT TO RF ATTACHMENT

(mount adapter not needed)

CN-R85mm T1.3 L F
with EOS C70



CN-R85mm T1.3 L F
with EOS R5 C



CLEARLY VISIBLE DISTANCE INDICATOR

As a key feature of the Cinema Lens, the focus ring can mark numbers on both the left and right sides of the lens, so the distance indicator can be checked from both sides.

CHANGEABLE "FT" AND "M" DISPLAY UNITS

Switchable exterior parts allow users to swap distance markers between feet and meters.



PHOSPHORESCENT INDICATORS

To improve visibility in nighttime and dark area shooting, indicator markings with phosphorescent paint have been adopted for the front barrel (for right-side viewing).

PERIPHERAL LIGHT CORRECTION/CHROMATIC ABERRATION CORRECTION



These image correction features can be turned on or off based on registered lens information.

LENS INFORMATION DISPLAY/RECORDING

Lens information can be displayed on the viewfinder, and metadata such as lens name and position can be recorded in the image.

Focal length information




T No.

DUAL PIXEL FOCUS GUIDE

During manual focus, the Dual Pixel Focus Guide can be displayed using distance measurement information and lens distance information.

The Dual Pixel Focus Guide lets users see front and back focus at a glance for smooth and precise focusing.



FRONT FOCUS FOCUSED BACK FOCUS

SPECIFICATIONS

		CN-R14mm T3.1 L F	CN-R20mm T1.5 L F	CN-R24mm T1.5 L F	CN-R35mm T1.5 L F	CN-R50mm T1.3 L F	CN-R85mm T1.3 L F	CN-R135mm T2.2 L F
Mount		RF mount						
Focal length		14 mm	20 mm	24 mm	35 mm	50 mm	85 mm	135 mm
Maximum diameter ratio (T-number)		1:3.1	1:1.5	1:1.5	1:1.5	1:1.3	1:1.3	1:2.2
Number of iris blades		11 blades						
Angle of view	Aspect ratio 1.5:1 Screen dimensions 36.0x24.0mm 36.0x24.0mm	104.3° x 81.2°	84.0° x 61.9°	73.7° x 53.1°	54.4° x 37.8°	39.6° x 27.0°	23.9° x 16.1°	15.2° x 10.2°
	Aspect ratio 1.78:1 Screen dimensions 24.6x13.8mm	82.6° x 52.5°	63.2° x 38.1°	54.3° x 32.1°	38.7° x 22.3°	27.6° x 15.7°	16.5° x 9.3°	10.4° x 5.9°
Minimum shooting distance		0.2 m / 8"	0.3 m / 12"	0.3 m / 12"	0.3 m / 12"	0.45 m / 18"	0.95 m / 3'2"	1 m / 3'4"
Shooting range at closest approach	Aspect ratio 1.5:1 Screen dimensions 36.0x24.0mm	24.8 x 16.5 cm	33.8 x 22.5 cm	28.8 x 19.2 cm	20.1 x 13.4 cm	24.9 x 16.6 cm	34.3 x 22.9 cm	21.1 x 14.1 cm
	Aspect ratio 1.78:1 Screen dimensions 24.6x13.8mm	16.9 x 9.5 cm	23.1 x 13.0 cm	19.7 x 11.0 cm	13.7 x 7.7 cm	17.0 x 9.5 cm	23.4 x 13.1 cm	14.4 x 8.1 cm
Front diameter		ø114 mm						
Image circle		ø43.3 mm						
Dimensions (w x h x d)		Appx. 118.4 x 118.4 x 118.0 mm	Appx. 118.4 x 118.4 x 125.5 mm	Appx. 118.4 x 118.4 x 125.5 mm	Appx. 118.4 x 118.4 x 125.5 mm	Appx. 118.4 x 118.4 x 125.5 mm	Appx. 118.4 x 118.4 x 125.5 mm	Appx. 118.4 x 118.4 x 139.6 mm
Weight		Appx. 1.3 kg	Appx. 1.4 kg	Appx. 1.3 kg	Appx. 1.3 kg	Appx. 1.2 kg	Appx. 1.5 kg	Appx. 1.5 kg

Canon

Delighting You Always

SOUTH & SOUTHEAST ASIA REGIONAL HEADQUARTERS

CANON SINGAPORE PTE. LTD.

1 Fusionopolis Place, #14-10 Galaxis, Singapore 138522

Tel : 65-6799 8888

Fax : 65-6799 8882

<https://asia.canon>



RF Cinema Lens

CANON OFFICES

HONG KONG:

Canon Hong Kong Co. Ltd.

Tel : 852-3191 2333

Fax : 852-2428 3963

<https://hk.canon>

INDIA:

Canon India Pvt. Ltd.

Tel : 91-124-4160 000

Fax : 91-124-4160 011

<https://in.canon>

MALAYSIA:

Canon Marketing (Malaysia) Sdn. Bhd.

Local Customer Care Hotline : 1-800-88-2000

Fax : 603-5567 9441

Overseas Hotline : 603-2267 7374

<https://my.canon>

PHILIPPINES:

Canon Marketing (Philippines), Inc.

Customer Care Hotline : 63-2-884 9000

Provincial Hotline : 1-800-10-884 9000

<https://ph.canon>

SINGAPORE:

Canon Singapore Pte. Ltd.

Tel : 65-6799 8888

Fax : 65-6799 8882

<https://sg.canon>

TAIWAN:

Canon Marketing (Taiwan) Co., Ltd.

Customer Care Hotline : 0809-622 888

Fax : 886-2-6632 6700

<https://tw.canon>

THAILAND:

Canon Marketing (Thailand) Co. Ltd.

Tel : 66-2-3449 999

Fax : 66-2-3449 988

Customer Care Hotline: 66-2-3449 988

<https://th.canon>

VIETNAM:

Canon Marketing Vietnam Co., Ltd.

Ho Chi Minh City

Office & Showroom

Tel : 28-3820 0466

Fax : 28-3820 0477

<https://vn.canon>

Canon Singapore Pte Ltd. All rights reserved.

This document is for information purpose only and the contents are subject to change without notice.

Product options, name and availability may vary by regions. Nothing in this document should be construed

as a warranty. We expressly disclaim any liability or contractual obligations with respect to this document.



Dealer's Stamp